





AT-FH系列孔輸出型式

Hole Output Type

尺寸 (單節 1-stage, 減速比ratio i=1~5)



外形尺寸圖 Dimensions:



規格表 Specifications:

Unit: mm

尺寸 Sizes	AT065FH	AT075FH	AT090FH	AT110FH	AT140FH	AT170FH	AT210FH	AT240FH	AT280FH
D1	M4	M6	M6	M8	M10	M12	M16	M16	M16
D2 H7	13	14	18	22	32	40	50	55	60
D4 h7	63	73	88	108	135	165	205	235	275
D5	31	35	43	53	68	83	104	124	144
D7	21	22	28	33	47	55	75	85	110
D12	62	72	86	106	104	128	160	180	200
D14 h7	63	73	88	108	135	165	205	235	275
D15	62.9	72.9	87	107	105	127	158	178	198
L1	65	75	90	110	140	170	210	240	280
L3	13	14.5	15	15	15	15	20	25	25
L4	2	2	2	2	2	2	2	2	2
L7	47.5	54	62	72	87	102	127	147	167
L11	27	30	36	44	55	67	85	95	110
L13	13	15	15	15	15	15	20	25	25
L21	49	60.5	63	69.5	85.5	95	130	144.5	135
L22	81.5	98	108	124.5	155.5	180	235	264.5	275
L23	40	47	52	53	70	80	95	115	115
L24	30	32	35	35	50	55	65	80	80
C1°	46	70	100	100	130	165	215	215	235
C2°	M4	M5	M6	M6	M8	M10	M12	M12	M12
C3°	★ ≤11 / ≤12	★ ≤14 / ≤15.875 / ≤16	≤19	≤24	≤32	≤38	≤42	≤48	≤55
C4°	30	34	40	40	50	60	85	85	116
C5°	30	50	80	80	110	130	180	180	200
C6°	3.5	8	4	4	5	6	6	6	6
C7°	42	60	90	90	115	142	190	190	220
C8°	19.5	19	17	17	19.5	22.5	29	29	63
C9°	133.5	154.5	170	196.5	245	287.5	369	413.5	478
C10°	13.25	13.5	10.75	10.75	13	15	20.75	20.75	53.5
B3 P9	5	5	6	6	10	12	14	16	18
H3	15.3	16.3	20.8	24.8	35.3	43.3	53.8	59.3	64.4


9. C1~C10 是公制標準馬達連接板之尺寸, 請上網點選"減速機選用"找出正確之尺寸。

★ AT065 FHM1 提供 C3 ≤12 option. ★ AT075 FHM1 提供 C3 ≤16 option. ★ AT075 FHM2 提供 C3 ≤15.875 option.


AT-FH系列孔輸出型式

Hole Output Type

尺寸 (雙節2-stage, 減速比ratio $i=7\sim50$)



外形尺寸圖 Dimensions:



規格表 Specifications:

Unit: mm


尺寸 Sizes	AT065FH	AT075FH	AT090FH	AT110FH	AT140FH	AT170FH	AT210FH	AT240FH	AT280FH
D1	M4	M6	M6	M8	M10	M12	M16	M16	M16
D2 h_7	13	14	18	22	32	40	50	55	60
D4 h_7	63	73	88	108	135	165	205	235	275
D5	31	35	43	53	68	83	104	124	144
D7	21	22	28	33	47	55	75	85	110
D12	62	72	86	106	104	128	160	180	200
D14 h_7	63	73	88	108	135	165	205	235	275
D15	62.9	72.9	87	107	106	127	158	178	198
L1	65	75	90	110	140	170	210	240	280
L3	13	14.5	15	15	15	15	20	25	25
L4	2	2	2	2	2	2	2	2	2
L7	47.5	54	62	72	87	102	127	147	167
L11	27	30	36	44	55	67	85	95	110
L13	13	15	15	15	15	15	20	25	25
L21	75	84.5	99	122	144.5	157.5	206.5	239	248
L22	107.5	122	144	177	214.5	242.5	311.5	359	388
L23	40	47	52	53	70	80	95	115	115
L24	30	32	35	35	50	55	65	80	80
C1 ¹⁰	46	46	70	100	100	100	130	165	165
C2 ¹⁰	M4	M4	M5	M6	M6	M6	M8	M10	M10
C3 ¹⁰	≤12	≤12	≤16	≤24	≤24	≤24	≤32	≤38	≤38
C4 ¹⁰	30	30	34	40	40	40	50	60	60
C5 ¹⁰	30	30	50	80	80	80	110	130	130
C6 ¹⁰	3.5	3.5	8	4	4	4	5	6	6
C7 ¹⁰	42	42	60	92	92	92	115	142	142
C8 ¹⁰	21.5	21.5	21.5	20	20	20	24	31	31
C9 ¹⁰	161.5	181	210.5	252	304.5	347.5	440.5	510	559
C10 ¹⁰	14.5	14.5	15.5	13	13	13	16	21	21
B3 p_9	5	5	6	6	10	12	14	16	18
H3	15.3	16.3	20.8	24.8	35.3	43.3	53.8	59.3	64.4

10 C1~C10 是公制標準馬達連接板之尺寸, 請上網點選"減速機選用"找出正確之尺寸。


AT-FH系列孔輸出型式

Hole Output Type

尺寸 (三節 3-stage, 減速比ratio $i=75\sim500$)



外形尺寸圖 Dimensions:



規格表 Specifications:

Unit: mm

尺寸 Sizes	AT110FH	AT140FH	AT170FH	AT210FH	AT240FH	AT280FH
D1	M8	M10	M12	M16	M16	M16
D2 h7	22	32	40	50	55	60
D4 h7	108	135	165	205	235	275
D5	53	68	83	104	124	144
D7	33	47	55	75	85	110
D12	106	104	128	160	180	200
D14 h7	108	135	165	205	235	275
D15	107	106	127	158	178	198
L1	110	140	170	210	240	280
L3	15	15	15	20	25	25
L4	2	2	2	2	2	2
L7	72	87	102	127	147	167
L11	44	55	67	85	95	110
L13	15	15	15	20	25	25
L21	136.5	159.5	183.5	226	269	278
L22	191.5	229.5	268.5	331	389	418
L23	53	70	80	95	115	115
L24	35	50	55	65	80	80
C1 ¹¹	46	46	70	70	100	100
C2 ¹¹	M4	M4	M5	M5	M6	M6
C3 ¹¹	≤12	≤12	≤16	≤16	≤24	≤24
C4 ¹¹	30	30	34	34	40	40
C5 ¹¹	30	30	50	50	80	80
C6 ¹¹	3.5	3.5	8	8	4	4
C7 ¹¹	42	42	60	60	92	92
C8 ¹¹	21.5	21.5	21.5	21.5	20	20
C9 ¹¹	268	321	375	457.5	529	578
C10 ¹¹	14.5	14.5	15.5	15.5	13	13
B3 p8	6	10	12	14	16	18
H3	24.8	35.3	43.3	53.8	59.3	64.4

11. C1~C10 是公制標準馬達連接板之尺寸，請上網點選“減速機選用”找出正確之尺寸。

AT-F 輸入法蘭型系列

Input Flange Series



減速機性能資料 Files of Reducer Performance

規 格 Specification		節 數 Stages	比數 ¹ Ratio	AT065 FL AT065 FL1 AT065 FH AT065 FC AT065 FR1	AT075 FL AT075 FL1 AT075 FH AT075 FC AT075 FR1	AT090 FL AT090 FL1 AT090 FH AT090 FC AT090 FR1	AT110 FL AT110 FL1 AT110 FH AT110 FC AT110 FR1	AT140 FL AT140 FL1 AT140 FH AT140 FC AT140 FR1	AT170 FL AT170 FL1 AT170 FH AT170 FC AT170 FR1	AT210 FL AT210 FL1 AT210 FH AT210 FC AT210 FR1	AT240 FL AT240 FL1 AT240 FH AT240 FC AT240 FR1	AT280 FL AT280 FL1 AT280 FH AT280 FC AT280 FR1		
額定輸出力矩 T _{2N} Rated output torque	Nm	1	1	25	45	78	150	360	585	1,300	2,150	3,200		
			1.5	25	45	78	150	360	585	1,300	2,150	3,200		
			2	24	42	68	150	330	544	1,220	2,010	3,050		
			3	18	33	54	120	270	450	1,020	1,650	2,850		
			4	13	28	48	100	224	376	860	1,410	2,300		
			5	12	25	40	85	196	320	740	1,210	2,000		
		2	7	12	12	33	91	91	91	195	358	358		
			10	24	28	68	150	208	208	430	846	846		
			15	18	33	54	120	270	312	645	1,269	1,269		
			20	13	28	48	100	224	376	860	1,410	1,692		
			25	12	25	40	85	196	320	740	1,210	2,000		
			35	12	25	40	85	196	320	740	1,210	1,790		
			50	12	25	40	85	196	320	740	1,210	1,465		
		3	75	-	-	-	120	210	312	585	1,269	1,269		
			100	-	-	-	100	224	376	780	1,410	1,692		
			125	-	-	-	85	196	320	740	1,210	2,000		
			150	-	-	-	120	135	312	390	975	975		
			200	-	-	-	100	180	376	520	1,300	1,300		
			250	-	-	-	85	196	320	650	1,210	1,625		
			350	-	-	-	85	196	320	740	1,210	1,790		
		500	-	-	-	85	196	320	740	1,210	1,465			
最大加速力矩 T _{2B} Max. acceleration torque	Nm	1,2,3	1~500	1.5 倍額定輸出力矩 1.5 Times of Rated Output Torque										
最大加速輸入轉速 n _{1B} Max. acceleration input speed	rpm	1	1~5	7,500	6,500	5,500	4,500	3,500	3,000	2,200	2,000	1,700		
		2	7~50	8,000	8,000	6,000	6,000	6,000	6,000	4,800	3,600	3,600		
		3	75~500	-	-	-	8,000	8,000	6,000	6,000	6,000	6,000		
背隙* Backlash	arcmin	1	1~5	≤6	≤6	≤6	≤6	≤6	≤6	≤6	≤6	≤6		
		2	7~50	≤8	≤8	≤8	≤8	≤8	≤8	≤8	≤8	≤8		
		3	75~500	-	-	-	≤10	≤10	≤10	≤10	≤10	≤10		
容許徑向力 F _{2B} ² Permissible radial force 輸出軸d2 Output axis	N	1,2,3	1~500	900	1,100	1,700	2,700	4,800	6,600	11,500	16,000	18,000		
容許軸向力 F _{2aB} ² 輸出軸d2	N	1,2,3	1~500	450	550	850	1,350	2,400	3,300	5,750	8,500	9,000		
使用壽命 Service life	hr	1,2,3	1~500	20,000*										
效率 η Efficiency	%	1	1~5	≥98%										
		2,3	7~500	≥94%										
使用溫度 Operating temperature	°C	1,2,3	1~500	-10°C ~ 90°C										
潤滑 Lubrication				合成潤滑油脂 Fully Synthetic Grease										
噪音值 (n=1500rpm , 無負載) Noise value (non-loaded)	dB (A)	1,2,3	1~500	≤71	≤72	≤76	≤77	≤78	≤79	≤81	≤83	≤84		

1. 減速比 ($i=N_n/N_{out}$) Reduction Ratio

* 連續運轉降低使用壽命二分之一。

2. 作用於輸出軸中心位置 @ n_B

* 背隙值為在 2% 額定力矩 T_{2N} 的扭力下所測得

AT-F 輸入法蘭型系列

Input Flange Series

減速機轉動慣量 Rotary inertia of Reducer



規格 Specification		節數 Stage	比數 ¹ Ratio	AT065 FL AT065 FL1 AT065 FH AT065 FC AT065 FR1	AT075 FL AT075 FL1 AT075 FH AT075 FC AT075 FR1	AT090 FL AT090 FL1 AT090 FH AT090 FC AT090 FR1	AT110 FL AT110 FL1 AT110 FH AT110 FC AT110 FR1	AT140 FL AT140 FL1 AT140 FH AT140 FC AT140 FR1	AT170 FL AT170 FL1 AT170 FH AT170 FC AT170 FR1	AT210 FL AT210 FL1 AT210 FH AT210 FC AT210 FR1	AT240 FL AT240 FL1 AT240 FH AT240 FC AT240 FR1	AT280 FL AT280 FL1 AT280 FH AT280 FC AT280 FR1
轉動慣量 J_1 Rotary inertia	$\text{kg} \cdot \text{cm}^2$	1	1	0.51	1.30	3.14	7.62	23.54	59.09	195.96	365.38	787.63
			1.5	0.46	1.15	2.80	6.65	19.34	49.38	156.02	279.62	584.28
			2	0.44	1.10	2.68	6.23	17.72	45.44	140.80	245.78	500.26
			3	0.43	1.09	2.64	6.08	17.16	44.11	135.51	233.75	471.56
			4	0.43	1.08	2.63	6.05	17.03	43.79	134.14	230.77	464.76
			5	0.43	1.08	2.63	6.04	16.99	43.69	133.71	229.71	462.08
		2	7	0.15	0.15	0.50	2.79	2.79	2.79	9.91	29.26	29.26
			10	0.15	0.15	0.50	2.80	2.80	2.80	9.96	29.43	29.43
			15	0.15	0.15	0.50	2.80	2.80	2.80	9.96	29.43	29.43
			20	0.15	0.15	0.50	2.80	2.80	2.80	9.96	29.43	29.43
			25	0.15	0.15	0.50	2.80	2.80	2.80	9.96	29.43	29.43
			35	0.15	0.15	0.50	2.79	2.79	2.79	9.91	29.26	29.26
			50	0.15	0.15	0.50	2.79	2.79	2.79	9.89	29.20	29.20
		3	75	-	-	-	2.80	2.80	2.80	9.96	29.43	29.43
			100	-	-	-	2.80	2.80	2.80	9.96	29.43	29.43
			125	-	-	-	2.80	2.80	2.80	9.96	29.43	29.43
			150	-	-	-	2.79	2.79	2.79	9.89	29.20	29.20
			200	-	-	-	2.79	2.79	2.79	9.89	29.20	29.20
			250	-	-	-	2.79	2.79	2.79	9.89	29.20	29.20
			350	-	-	-	2.79	2.79	2.79	9.89	29.20	29.20
			500	-	-	-	2.79	2.79	2.79	9.89	29.20	29.20

重量 Weight

減速機型號 Reducer model		節數 Stage	比數 ¹ Ratio	AT065	AT075	AT090	AT110	AT140	AT170	AT210	AT240	AT280
FL 系列 FL Series	kg	1	1~5	2.8	4.4	7.1	12.1	20.9	36.1	69.4	101.2	158.3
		2	7~50	3.2	4.8	8.1	14.3	24.2	38.5	74.1	112.4	171.0
		3	75~500	-	-	-	13.9	23.7	38.8	73.4	110.2	168.7
FL1 系列 FL1 Series		1	1~5	2.7	4.3	7.1	11.9	20.3	35.5	68.3	99.6	156.0
		2	7~50	3.2	4.8	8.0	14.2	23.9	37.9	73.0	110.8	168.6
		3	75~500	-	-	-	13.8	23.4	38.2	72.3	108.6	166.4
FH 系列 FH Series		1	1~5	2.6	4.1	6.7	11.4	18.9	32.9	63.2	92.5	146.0
		2	7~50	3.1	4.6	7.7	13.6	22.4	35.3	67.9	103.7	158.7
		3	75~500	-	-	-	13.3	21.9	35.6	67.2	101.5	156.5
FC 系列 FC Series		1	1~5	2.9	4.4	7.2	11.8	20.4	35.0	66.5	96.0	151.7
		2	7~50	3.3	4.9	8.2	14.1	24.1	37.4	71.2	107.2	164.4
		3	75~500	-	-	-	13.7	23.5	37.5	70.5	105.0	162.2
FR1 系列 FR1 Series		1	1~5	2.7	4.3	7.1	11.9	20.3	35.5	68.3	99.6	156.0
		2	7~50	3.2	4.8	8.0	14.2	23.9	37.9	73.0	110.8	168.6
		3	75~500	-	-	-	13.8	23.4	38.2	72.3	108.6	166.4