

Hexagon Head Bolt with Block ▶ Straight/Adjustable type



Please order according to the diagram

①~③ Select the-Type and parameters in the order of for ordering

④ Straight type

Model(①Code) — ②S
UPKYO — S7

⑤ Adjustable type

Model(①Code) — ②M — ③L
UPLZO — M4 — L15



Discounted Price
Quantity 1~9 10~
Price 100% Separate Quotation
Price Excluding Tax (¥/unit)

④ Straight type

Code	Type	Thread	Main Body			Block		
			Material	Hardness	Surface Treatment	Material	Color	Hardness
UPKYO	Straight type	Coarse Thread	SCM435	46~50HRC	Electroless Nickel Plating	Polyurethane	Black	Shore hardness A90
UPKYP			SUS304	—	—	—	—	—

CAD 2D/3D

① Suitable for small to medium-sized moving and positioning mechanisms.
② Block features a bonding process for secure attachment.

Model		M	A	A ₁	L	d	(C)
Code	S						
UPKYO UPKYP	5.5	3	1.5	0.7	5	3.5	6.4
	7	4		1.5	—	5	8.1
	8	5			6	6	9.2
	10	6		—	—	8	11.5
	13	—	2	2	10	10	15
	14	8			—	—	16.2
	17	10			12	13	19.6
	19	12			15	15	21.9

⑤ Adjustable type

Code	Type	Thread	Main Body			Block		Accessories (One nut)	
			Material	Surface Treatment	Strength Grade	Material	Color	Material	Surface Treatment
UPLZO	Standard Type	Flat-ended Type	SCM435	Lustrous galvanized finish	10.9	Polyurethane	Black	Shore hardness A90	SS400
UPLZP			—	—	—	Polyformaldehyde	White	—	
UPLZQ			—	—	—	silicone	Light grey	Shore hardness A70	
UPLZR			—	—	—	Polyurethane	Black	Shore hardness A90	
UPLZS		Coarse Thread	SUS304	—	—	Polyformaldehyde	White	—	SUS304 equivalent
UPLZT			—	—	—	silicone	Light grey	Shore hardness A70	—
UPLZU			—	—	—	—	—	—	—
UPLAO			—	—	—	—	—	—	—
UPLAP	Hexagon socket type	SR Type	SCM435	Lustrous galvanized finish	10.9	Polyurethane	Black	Shore hardness A90	SS400
UPLBO			SUS304	—	—	—	—	—	SUS304 equivalent
UPLBP			—	—	—	—	—	—	—
UPLBQ			—	—	—	—	—	—	—
UPLBR		Flat-ended Type	SCM435	Lustrous galvanized finish	10.9	Polyurethane	Black	Shore hardness A90	SS400
UPLBS			SUS304	—	—	Polyformaldehyde	White	—	SUS304 equivalent
UPLBT			—	—	—	—	—	—	—
UPLBT			—	—	—	—	—	—	—

Standard Type
Flat-ended Type

Standard Type
SR Type

Hexagon socket type
Flat-ended Type

Hexagon socket type
SR Type

① Suitable for small to medium-sized moving and positioning mechanisms.
② Block features a bonding process for secure attachment.

Model		M	L								d	SR	A	A ₁	A ₂	A ₃	S	S ₁	(C)	T	V
Code			15	20	25	30	35	40	45	50											
Standard Type	Hexagon socket type	3*	15	20	25	30	35	40	—	—	3.5	3.5	2	—	0.7	2	5.5	—	6.4	2.4	—
UPLZO	UPLZS	4	15	20	25	30	35	40	—	—	5	5	2.8	1.5	—	2.2	7	2	8.1	3.2	2.2
UPLZP	UPLZT	5	15	20	25	30	35	40	45	50	6	6	3.5	—	—	2.3	8	2.5	9.2	4.5	2.8
UPLZQ	UPLZU	6	20	25	30	35	40	45	50	60	8	8	4	—	—	2.6	10	3	11.5	5	3
UPLZR	UPLBQ	8	20	25	30	35	40	45	50	60	10	10	5.5	2	2	2.8	13	4	15	6.5	4
UPLBR	UPLBS	10	20	25	30	35	40	45	50	60	13	13	7	—	—	3.2	17	5	19.6	8	5
UPLAP	UPLBT	12*	30	40	50	60	70	—	—	—	15	15	8	—	—	3.5	19	—	21.9	10.5	—

① Hex Socket Drive without Tape * Specifications