

Universal Swivel Lifting Eye



Please order according to the diagram

1~2 Select the-Type and parameters in the order of for ordering

Model(1Code) - (2)Specification

USCQO

0.4T




Price Excluding Tax (Yuan)

Discounted Price

Quantity 1~9 10~
Price 100% Separate Quotation



CAD 2D 3D




Code	Type	Material	Surface Treatment
USCQO	Universal Swivel Lifting Eye	Alloy Steel	Baking Finish

① Due to the baking process, some areas of the product at the lifting point may not be baked.

Model		M	A	B	C	D	E	F	G	K	Net weight (kg)
Code	Specification										
USCQO	0.4T	8	29	32	40	8	12	72	35	30	0.2
	0.6T	10					15				0.3
	0.7T	12	35		45	10	18	95	40	36	0.84
	1.5T	16		50	54		24	104	46	41	1.3
	2.5T	20	38		68	13	30	122	62	55	1.4
	4T	24	40	66	88	19	36	154	78	70	2.6

Working Limit Load

Rings Installation Method												
Number of rings			1	2	1	2	2	2	2	3~4	3~4	3~4
Lifting Angle			0°	0°	90°	90°	0~45°	45~60°	Asymmetrical	0~45°	45~60°	Asymmetrical
Model			Threaded	Working Limit Load (Tons)								
Code	Specification											
USCQO	0.4T	M8	0.6	1.2	0.4	0.8	0.4	0.3	0.3	0.6	0.4	0.3
	0.6T	M10	0.9	1.8	0.6	1.2	0.6	0.4	0.4	0.9	0.6	0.4
	0.7T	M12	1.2	2.4	0.7	1.5	0.8	0.6	0.6	1.2	0.9	0.6
	1.5T	M16	2.6	5.2	1.5	3	1.8	1.3	1.3	2.7	1.9	1.3
	2.5T	M20	4	8	2.5	5	2.8	2	2	4.2	3	2
	4T	M24	7	14	4	8	4.9	3.5	3.5	7.3	5.2	3.5