

Screws/Nuts/
Washers/Eye Bolts



1.12T

USKXO

1T




Price	100 %	Separate Quantities
-------	-------	---------------------

Technical drawing of a hook with dimensions and a 3D model. The drawing includes a 3D perspective view of the hook on the left and a 2D cross-sectional view on the right. The 2D view shows the internal structure of the hook, including the shank, the throat, and the hook body. Dimensions are labeled as follows:

- A**: Total height of the hook body.
- D**: Diameter of the shank.
- B**: Width of the throat.
- K**: Total height of the hook body.
- P**: Thickness of the hook body.
- H**: Height of the hook body.
- I**: Width of the hook body.

! Due to the baking process, some areas of the product at the lifting point may not be baked.

Model		Working Load Limit (Tonnes)	Safety Factor	Gate Ø / Chain Shackle (mm)											Net weight (kg)
Code	Specification														
USJWO	1.12T	1.12	4	6	149	29	22	31	12	15	19	0.7			
	2.0T	2.0		7.8	186	34	29	36	14	20	24	1.2			
	3.15T	3.15		10	220	44	34	40	16	26	30	2.0			
	5.3T	5.3		13	267	52	43	46	22	30	39	4.1			



Features:

- The lifting hooks are quenched and tempered;
- Conduct 20,000-cycle fatigue test under 1.5 times the working load limit tension;
- All lifting hooks undergo 100% electromagnetic flaw detection testing;
- The lifting hooks undergo standard certification tests under 2 times the working load limit tension;
- The **USKXO** hooks with brass washer type serve as a positioning device, which is non-rotatable under load;
- The **USKYO** hooks with ball bearing type enable full 360° rotation under load.

Products produced in different batches may exhibit color variations.

 Due to the baking process, some areas of the product at the lifting point may not be baked.

Model		Working Load Limit (Tonnes)	Safety Factor	A	B	C	D	G	H	K	L	P	P ₁	T	Net weight (kg)
Code	Specification														
USKXO USKYO	1T	1	5	32	23	25	12	78	19	123	154	26	22	16	0.6
	1.5T	1.5						80	21	126	158	24	19	18	0.7
	2T	2						91	25	143	181	27	20	22	1.0
	3T	3						102	29	196	212	31	25	24	1.5
	5T	5						130	36	211	269	36	31	31	3.2




USLZO

1.12T



Price	100%	Separate Quotation
-------	------	--------------------



 Products produced in different batches may exhibit color variations.

Model	Working Load Limit (Tonnes)	Safety Factor	Grade 60 Chain Shackle (mm)	K	A	D	B	Net weight (kg)	
Code	Specification								
USLZO	1.12T	1.12	4	6	44	15	7	17	0.08
	2.0T	2.0		7.8	57	18	9	22	0.2
	3.15T	3.15		10	68	25	11	26	0.3
	5.3T	5.3		13	91	30	16	35	0.7