

Hole Retaining Ring ▶ C-Type Reverse Hole Retaining Ring



Please order according to the diagram

①~② Select the-Type and parameters in the order of for ordering

Model(①Code) — ②Specification

URJHO — 10




Discounted Price	
Quantity	Price
1~9	100%
10~	Separate Quotation

Price Excluding Tax (¥/mm)




CAD 2D 3D



Retaining Ring Dimensions



This chart applies to sizes up to 12



Retaining Ring Assembly Dimensions



Specification	r(max)
26 or more	0.13
Less than 26	0.25

Model		Retaining Ring Dimensions								For shafts						
Code	Specification	d ₃		d ₄	t		b	d ₀	Tolerance	d ₅	d ₁	d ₂		n		m
		Basic Dimension	Limit Deviation		Basic Dimension	Limit Deviation						Basic Dimension	Limit Deviation	Basic Dimension	Limit Deviation	
URJHO	10	11.1		7.7			1.7			5.9	10	10.4				
	11	12.2		8.6						6.6	11	11.4				
	12	13.3		9.7			1.8			7.6	12	12.5				
	13	14.1	±0.18	10.9			1.6			9	13	13.6				
	14	15.1		11.7			1.7	0.9		9.8	14	14.6				
	15	16.2		12.6			1.8		±0.3	10.6	15	15.7				
	16	17.3		13.5	1	±0.05	1.9			11.4	16	16.8		1.15		1.5
	17	18.3		14.3			2			12.2	17	17.8				
	18	19.5		15.3			2.1			13	18	19				
	19	20.5		16.1			2.2	1		13.8	19	20				
	20	21.5		16.9			2.3			14.5	20	21				
	21	22.5	±0.2	17.7						15	21	22				
	22	23.5		18.7			2.4			16	22	23		±0.21 0		
	24	25.9		20.7			2.6			17.5	24	25.2				
	25	26.9		21.5			2.7			18.5	25	26.2				1.8
	26	27.9		22.3			2.8			19	26	27.2				
	28	30.1		24.1	1.2		3			20.5	28	29.4				2.1
	30	32.1		25.7			3.2	1.4		22.5	30	31.4				
	32	34.4		27.4		±0.06	3.5		±0.4	23.5	32	33.7				2.55
	34	36.5	±0.25	29.1			3.7			25	34	35.7				
	35	37.8		30			3.9			26	35	37				
	36	38.8		30.8	1.5		4			26.5	36	38		1.65	±0.14 0	3
	37	39.8		31.6			4.1			27.5	37	39		±0.25 0		
	38	40.8		32.4			4.2			28	38	40				
	40	43.5		34.7			4.4			30	40	42.5				
	42	45.5	±0.4	36.3			4.6			31	42	44.5				
	45	48.5		38.9	1.75		4.8	2		33	45	47.5			1.9	3.75
	47	50.5		40.7			4.9			35	47	49.5				
	48	51.5		41.5			5			36	48	50.5				
	50	54.2		44		±0.07	5.1			38	50	53				
	52	56.2		45.8			5.2	2.2		40	52	55				
	55	59.2		48			5.6		±0.5	42	55	58				
	56	60.2		48.8	2		5.7			43	56	59			2.2	
	58	62.2	±0.45	50.4			5.9	2.5		44	58	61		±0.3 0		
	60	64.2		52			6.1			46	60	63				
	62	66.2		53.6			6.3	2.8		47	62	65				4.5
	65	69.2		55.8			6.7			49	65	68				
	68	72.5		58.5			7			52	68	71				
	72	76.5		61.7	2.5	±0.08	7.4			55	72	75			2.7	
	75	79.5		63.9			7.8			57	75	78				
	78	82.5		66.3			8.1			59	78	81				
	80	85.5		68.9			8.3		±0.7	61	80	83.5				
	85	90.5	±0.55	72.7			8.9			64	85	88.5		±0.35 0		
	90	95.5		76.7	3	±0.09	9.4	4		68	90	93.5			3.2	±0.18 0
	100	105.5		84.5			10.5			76	100	103.5				5.25