

Stop Pin ▶ Spherical Surface Type • Threaded Type Internal/External Thread Mounting Type



Please order according to the diagram

①~③ Select the type and parameters in the order of for ordering

■ Dimension Fixed Type

Model(●Code) — ●B
KACEQ — B5.5

■ Dimension Specified Type

Model(●Code) — ●B — ●H
KACES — B5.5 — H2





● Discounted Price
Quantity 1~9 10~
Price 100% Separate Quotation
Price Excluding Tax (Tax)

■ Spherical Surface Type



CAD 2D 3D

Code	Type	Material		Hardness	Surface Treatment
		National Standard	Equivalent		
KACEQ	Spherical Surface Type	35CrMo	SCM435	40 ~ 45HRC	Electroless Nickel Plating
KACER		9Cr18Mo	SUS440C		—
KACES	Dimension Specified Type	35CrMo	SCM435		Electroless Nickel Plating
KACET		9Cr18Mo	SUS440C		—



① SUS440C Material may discolor due to quenching.

■ Dimension Fixed Type

Model	B	H	M	L	(C)	T	SR
Code	B						
KACEQ KACER	5.5	5	3	5	6.4	4.3	7.5
	7		4		8.1	4	8.5
	8		5	6	9.2	3.9	10
	10	8	6	9	11.5	6.5	12
	10B						
	13						
	14	10	8	10	15	6.1	16
	14B			12	16.2		18
	17						
	19	12	10	12	19.6	7.7	22
	19B		12	15	21.9	7.5	25

■ Dimension Specified Type

Model	B	H	M	L	(C)	T	SR
Code	B	Minimum Unit 0.1					
KACES KACET	5.5	2.0~12.0	3	5	6.4	H-0.7	7.5
	7		4		8.1	H-1	8.5
	8		5	6	9.2	H-1.1	10
	10	5.0~32.0	6		11.5	H-1.5	12
	13		8	10	15	H-1.9	16
	14				16.2		18
	17	10.0~52.0	10	12	19.6	H-2.3	22
	19		12	15	21.9	H-2.5	25



Please order according to the diagram

①~③ Select the type and parameters in the order of for ordering

Model(●Code) — ●D — ●L
KADAP — D10 — L19







● Discounted Price
Quantity 1~9 10~
Price 100% Separate Quotation
Price Excluding Tax (Tax)



CAD 2D 3D

Internal Thread Mounting Type		External Thread Mounting Type		Material		Surface Treatment
Ball joint type	Ball-tip Cone Type	Ball joint type	Ball-tip Cone Type	National Standard	Equivalent	
KADAP	KADBP	KADFP	KADGP	45	S45C	—
KADAR	KADBR	KADFR	KADGR	0Cr18Ni9	SUS304	



■ Internal Thread Mounting Type

Model	D	L	M	R	d
Code	D	Minimum Unit 1			
Ball joint type	6	19~120	3	1	2
	8	19(24)~120	4	1.5	
	10	19(26)~120			
	12	21(32)~120	5	2	2.5
Ball-tip Cone Type	15	25(40)~120	6	3	5
	20	28(47)~120			
	25	31(57)~120			

■ External Thread Mounting Type

Model	D	L	N	R	d
Code	D	Minimum Unit 1			
Ball joint type	10	19(26)~120	5		
	12	20(32)~120	6	2	3.5
	15	25(40)~120	8		
	20	27(47)~120	10	3	5
	25	30(57)~120			

① Ball-tip Cone Type, L Dimension refers to internal size.

① Ball-tip Cone Type, L Dimension refers to internal size.