

Non-Spring Locating Bead ▶ Hex Socket Bolt Type



Please order according to the diagram

①~③ Select the type and parameters in the order of for ordering

Model(①Code) — ②M — ③Nominal Size
TBACP — M4 — 12




Price Excluding Tax (Yen)

Discounted Price

Quantity 1~9 10~
Price 100% Separate Quotation



CAD 2D 3D



Code	Type	Main Body			Ball joint	
		Material	Hardness	Surface Treatment	Material	Hardness
TBACP	Hex Socket Bolt Type	SCM435	35~45HRC	Black Oxide Finish	SUJ2	53~60HRC
TBACQ		SUS304	—	—	SUS440C	55HRC~

Model Code	M	Nominal Size	L	L ₁	D	K	S	h	d	H	Load-bearing Capacity (kN)
TBACP TBACQ	4	10	10.5	2.1	7	4	3	2	2.5	0.8	1.3
		12	12.5								
		16	16.5								
		20	20.5								
		25	25.5								
	5	12	12.6	2.4	8.5	5	4	2.5	3	1	1.4
		16	16.6								
		20	20.6								
		25	25.6								
		30	30.6								
	6	16	16.8	3	10	6	5	3	4	1.3	3.3
		20	20.8								
		25	25.8								
		30	30.8								
		40	40.8								
	8	20	21.2	3.5	13	8	6	4	5.5	1.8	3.9
		30	31.2								
		35	36.2								
		40	41.2								
		50	51.2								
	10	25	26.7	4.5	16	10	8	5	7	2.3	3.4
		30	31.7								
		40	41.7								
		50	51.7								
		60	61.7								
	12	30	32	5	18	12	10	6	8.5	2.8	4.8
		50	52								
		80	82								