

Positioning Pin/Bushings for locating pins ▶ With Vent Hole • Internal Thread Type Flange type



Please order according to the diagram

①~③ Select the type and parameters in the order of for ordering

Model(①Code) - ②Dg6 - ③L
BDMAG - D6 - L12



Discounted Price
Quantity 1~9 10~
Price 100% Separate Quotation

Price Excluding Tax (Yuan)

Internal Thread Type

Internal Thread Type	Material		Hardness	Surface Treatment
	International	Equivalent		
BDMAG	GCr15	SUJ2	Quenching Hardness 43~48HRC	—
BDMAJ	—	—	Quenching Hardness HRC56~, Coating Hardness 850HV~	Hard Chromium Plating, Coating Thickness 3~5μm
BDMAS	0Cr18Ni9	SUS304	—	—
BDMAT	9Cr18Mo	SUS440C	Quenching Hardness 48~53HRC	—

Model		L	M	V ₁	V ₂	r
Code	D _{g6}					
BDMAG	5	10 12 15 20 25 30	M3	6	1.0	1.0
BDMAJ	6	10 12 15 20 25 30	M4	8	1.5	1.5
BDMAS	8	10 12 15 20 25 30	M5	10	2.0	2.0
BDMAT	10	15 20 25 30	M6	10	2.0	2.0
	12	15 20 25 30				

① D=6, L=10 When, V₁=6. ② When L<V₁<6, there may be a situation where the threaded bottom hole runs through.



Please order according to the diagram

①~③ Select the type and parameters in the order of for ordering

Model(①Code) - ②P - ③L
BEKAQ - P5 - L10



Discounted Price
Quantity 1~9 10~
Price 100% Separate Quotation

Price Excluding Tax (Yuan)

Bushings for locating pins. Flange type

Round Flange Type	Square Flange Type	Opposite Edge Flange Type	Material		Hardness	Surface Treatment
			International	Equivalent		
BEKAQ	BEKBQ	BEKCQ	9CrWMn	SKS3	Quenching Hardness 54~58HRC	—
BEKAR	—	BEKCR	—	—	—	Electroless Nickel Plating

Model	P	L	R	S	K	W	T	D _{g6}	A	d	d ₁	h
Round Flange Type	5	8 10 12 16	1	25	20	12	5	10	17	3.3	6.5	3.5
BEKAQ	6	10 12 16 20	—	28	22	15	—	12	20	—	—	—
BEKAR	8	—	—	36	28	22	—	15	26	—	—	—
BEKBQ	10	—	—	40	31	25	6	18	30	4.5	8	4.5
Square Flange Type	12	12 16 20 25 30	2	44	34	30	—	22	34	—	—	—
BEKCQ	13	—	—	56	44	35	—	25	42	6.6	11	6.5
BEKCR	15	—	—	60	47	40	8	26	46	—	—	—
Opposite Edge Flange Type	16	16 20 25 30 35	3	—	—	—	—	30	—	—	—	—
BEKDQ	20	20 25 30 35 40	—	—	—	—	—	35	—	—	—	—
BEKDR	25	—	—	—	—	—	—	—	—	—	—	—