

Square Bracket for Base

Standard Type · Oblong Hole Type/Simplified Type/Without Flange Type Side Mount Type



①~② Select the type and parameters in the order for ordering.

■ Simplified Type

Model(①Code)

KWAHA

— ●DH7

D20

■ Without Flange Type

Model(①Code)

KWAIA

— ●DH7

D10



● Discounted Price

| | | |
|----------|------|--------------------|
| Quantity | 1-9 | 10- |
| Price | 100% | Separate Quotation |

Mounting Base
Base - Post Changes

31

CAD 2D/3D

| Side Mount Type | | Material | | Surface Treatment | Accessory(Screws) |
|-----------------|------------------|---------------|------------|----------------------------|---|
| Standard Type | Oblong Hole Type | International | Equivalent | | |
| KWAHA | KWAIA | Q235 | SS400 | Black Oxide Finish | Hex Socket Head Cap Screw |
| KWAHB | KWAIB | | | Electroless Nickel Plating | Hex Socket Head Cap Screw (Stainless Steel) |
| KWAHC | | LF2 | A5052 | Black Anodizing | Hex Socket Head Cap Screw |
| KWAHD | KWAIC | | | Natural Anodizing | Hex Socket Head Cap Screw (Stainless Steel) |
| KWAHE | KWAID | 0Cr18Ni9 | SUS304 | — | — |

Standard Type

Oblong Hole Type

Standard Type · Oblong Hole Type

| Model | | A | B | L | T | G | F | F ₁ | J | K | h | H | E | d | d ₁ | Z | M | W | |
|---------------|------------------|------|-----|-----|----|----|----|----------------|-------|------|-----|----|------|----|----------------|------|----|-----|---|
| Standard Type | Oblong Hole Type | (10) | 40 | 35 | 32 | 10 | 18 | 30 | | | 4.4 | 15 | 10.5 | 20 | 5.5 | 9 | 6 | M5 | |
| | | (12) | 44 | | | | | 34 | | | 5.5 | 14 | 11.5 | 22 | | | | | |
| | | (15) | 50 | 40 | 38 | | | 20 | 38 | | | 18 | 12.5 | 25 | 6.6 | 11 | 7 | M6 | 2 |
| | | (16) | 50 | 40 | 38 | 12 | | | | | 6.6 | 18 | 12.5 | 25 | | | | | |
| | | 20 | 65 | 45 | 45 | | | 25 | 50 | 47.5 | 5.5 | 22 | 15 | 30 | | | | | |
| | | 25 | 80 | 60 | 53 | | | 36 | 60 | 57.5 | | 27 | 18 | 35 | | | | | |
| | | 30 | 90 | 60 | 60 | | | 36 | 70 | 67.5 | 7.5 | 30 | 21 | 45 | | | | | |
| | | 35 | 105 | 80 | 68 | 15 | | 40 | 80 | 77.5 | | 35 | 24 | 50 | 9 | 14 | 9 | M8 | |
| | | 40 | 115 | 80 | 76 | | | 40 | 90 | 87.5 | 9.5 | 38 | 27 | 60 | | | | | |
| | | 50 | 135 | 100 | 87 | 18 | 50 | 105 | 102.5 | 12.5 | 14 | 43 | 33 | 70 | 11 | 17.5 | 11 | M10 | 3 |

① The specifications within () do not apply to oblong hole types.

Simplified Type/Without Flange Type

CAD 2D/3D

| Side Mount Type | | Material | | Surface Treatment | Accessory(Screws) |
|-----------------|---------------------|---------------|------------|----------------------------|---|
| Simplified Type | Without Flange Type | International | Equivalent | | |
| KWAJA | KWAKA | Q235 | SS400 | Black Oxide Finish | Hex Socket Head Cap Screw |
| KWAJB | KWAKB | | | Electroless Nickel Plating | Hex Socket Head Cap Screw (Stainless Steel) |
| KWAJC | KWAKC | LF2 | A5052 | Black Anodizing | Hex Socket Head Cap Screw |
| KWAJD | KWAKD | | | Natural Anodizing | Hex Socket Head Cap Screw (Stainless Steel) |
| KWAJE | KWAKE | 0Cr18Ni9 | SUS304 | — | — |

Simplified Type

Without Flange Type

Simplified Type

| Model | | A | B | L | T | F | G | K | h | H | E | d | d ₁ | Z | M | W |
|---------------|-----------------|----|-----|----|----|----|----|-----|----|----|----|-----|----------------|------|----|-----|
| Standard Type | Simplified Type | 20 | 60 | 30 | 45 | 45 | 18 | 6.6 | 22 | 15 | 30 | 6.6 | 11 | 6.5 | M6 | 2 |
| | | 25 | 73 | 45 | 53 | 54 | 30 | 9 | 27 | 18 | 35 | | | | | |
| | | 30 | 83 | 45 | 60 | 64 | 30 | 9 | 30 | 21 | 45 | 9 | 14 | 9 | M8 | |
| | | 35 | 94 | 60 | 68 | 72 | 35 | 11 | 35 | 24 | 50 | | | | | |
| | | 40 | 104 | 76 | 76 | 82 | 38 | 11 | 38 | 27 | 60 | | | | | |
| | | 50 | 118 | 75 | 87 | 18 | 94 | 45 | 14 | 43 | 33 | 70 | 11 | 17.5 | 11 | M10 |

Without Flange Type

| Model | | A | B | M | N | N ₁ | Z ₁ | h | H | E | d | d ₁ | Z | M ₁ | Accessory (Screws) |
|---------------|---------------------|------|----|----|----|----------------|----------------|------|------|-----|-----|----------------|----|----------------|--------------------|
| Standard Type | Without Flange Type | (10) | 35 | M4 | 10 | 8 | 18 | 10.5 | 15.5 | 5.5 | 8 | 4.5 | M4 | M4-L20 2个 | |
| | | (12) | 38 | M5 | 12 | 10 | 20 | 11.5 | 18.5 | 5.5 | 9.5 | 5.5 | M5 | M5-L25 2个 | |
| | | (15) | 45 | M6 | 13 | 12 | 25 | 12.5 | 22.5 | 6.6 | 11 | 6.5 | M6 | M6-L35 2个 | |
| | | 20 | 53 | M6 | 18 | 25 | 30 | 15 | 29.5 | | | | | M6-L40 2个 | |
| | | 25 | 59 | M8 | 17 | 33 | 33 | 18 | 34.5 | | | | | M8-L45 2个 | |
| | | 30 | 67 | M8 | 29 | 36 | 37 | 21 | 44.5 | 9 | 14 | 9 | M8 | M8-L50 2个 | |

① KWAKC/AK/D/AKE No Specification with () ② D_{H7} tolerance and perpendicularity are tolerances before opening.
③ The recommended tolerances for mating shafts are g6 and f8