

Mounted Bearing ▶ Ball bearings with suspension housing/Adjustable diamond housing outer spherical surface Cast Type



Please order according to the diagram


①~② Select the type and parameters in the order of for ordering

Model(①Code) — ②Specification
YBNV — 201

Model(①Code) — ②Specification
YBOU — 201




Discounted Price
Quantity 1~9 10~
Price 100% Separate Quotation
Price Excluding Tax (¥/unit)



Concave Spherical Surface Tolerance of Bearing Housing: Clearance Fit

Model	International Model	d	H	L	J	A	A ₁	A ₂	D	E	Z	P	B	N	G	S	Installation Hole Size Tolerance	Deviation Installation Hole Position	Locking Screw	Maximum Tightening Torque (N.m)	Basic Rated Load(N) Dynamic Load C _r	Static Load C _{0r}	Weight (g)
Code	Specification																						
YBNV	201	UCFB201	12																				520
	202	UCFB202	15																				500
	203	UCFB203	17	109	52	32	52	42	27	60	33.3	25.5	15	31									490
	204	UCFB204	20												10								470
	205	UCFB205	25	116	56	34		45		68	35.7	27	16	34									660
	206	UCFB206	30	132	65	40	55	50	29	80	40.2	31	18	38.1									950
	207	UCFB207	35	144	70	46	62	55	32	90	44.4	33	19	42.9									1270
	208	UCFB208	40	164	78	50	72	60	41	100	51.2	35	21	49.2									1710
	209	UCFB209	45	175	80	54	76	65	43	108	52.2	38	22	51.6									2280
	210	UCFB210	50	184	86	58	82	68	46	114	54.6	39											2300



Concave Spherical Surface Tolerance of Bearing Housing: Clearance Fit

Model	International Model	d	L	J	H	A	A ₁	A ₂	E	N	S	B	Z	Installation Hole Size Tolerance	Deviation Installation Hole Position	Locking Screw	Maximum Tightening Torque (N.m)	Basic Rated Load(N) Dynamic Load C _r	Static Load C _{0r}	Weight (g)
Code	Specification																			
YBOU	201	UCFA201	12																	430
	202	UCFA202	15																	410
	203	UCFA203	17	98	78	50	24	11	13.74	59	10	12.7	31	32.04						400
	204	UCFA204	20																	380
	205	UCFA205	25	122	96	64	27	13	16	70		14.3	34	35.7						650
	206	UCFA206	30	141	115	68	30.5	14	18	80	12	15.9	38.1	40.2						960
	207	UCFA207	35	155	128	75	33	15	19	92	13	17.5	42.9	44.4						1270
	208	UCFA208	40	171	144	84	38	14	21	105	19	19.2	51.2							1800
	209	UCFA209	45	178	146	88		16	22	108		19	52.2							1910
	210	UCFA210	50	188	155	92	39			114	16		54.6							2090