

Mounted Bearing ▶ Double bearing flange type

Retainer type with L size specification



Please order according to the diagram

①~④ Select the type and parameters in the order of for ordering


Model(①Code) — ②Bearing Model — ③Seal ring — ④L — NA

YCEKO — 6800 — vv — L40 — NA

Optional Processing




Discounted Price
Quantity 1~9 10~
Price 100% Separate Quotation
Price Excluding Tax (¥/unit)




CAD 2D 3D

Type			Material		Surface Treatment
Round Flange Type	Square Flange Type	Opposite Edge Flange Type	Bearing	Bearing Housing	Bearing Housing
YCEKO	YCELO	YCEMO	Steel	S45C	Spring steel
YCEKP	YCELP	YCEMP			Black Oxide Finish
YCEKT	—	YCEMT		Electroless Nickel Plating	
YCEKU	—	YCEMU	Stainless Steel	A2017	SUS304
YCEKQ	YCELQ	YCEMQ			
				SUS304	—


□ Bearing accuracy: GB/T 307.10 Grade, Equivalent to JIS B 15140 Grade.




Round Flange Type



Square Flange Type



Opposite Edge Flange Type



Model			Minimum Unit 1	d	D _{H7}	B	V	H	W	T	dh	D _{1g7}	P.C.D	K	A	F	d ₁	d ₂	H ₁
Code	Bearing Model	Seal Rings	L																
Round Flange Type	623			3	10	^{+0.015} ₀	4		33	16	7	7	14		24	27	24		
	624		20~40	4	13				35	18		9	17	^{-0.006} _{-0.024}	26	30	26		6.5
	605			5	14	^{+0.018} ₀	5		36	20		10	18					3.7	
	625		20~30		16				38	22		12	20		28	31	28		
	606		20~40	6	17		2.65		39	23		13	21		29	32	29		
	626		30~50		19		6		41	25		15	24		31	34	31		
	698		25~50											^{-0.007} _{-0.028}	35	36	35		
	608		20~50	8	22		7		45	29		18	27		37	37	37		
	628		30~50		24		8	2.85	47	32		20	30		37	37	37		
	6800		20~40		19		5	2.65	41	25		15	24		31	34	31		
	6900		25~60		22		6		45	29		19	27		35	36	35		
	6000		30~60	10	26	^{+0.021} ₀	8		50	34		22	32	^{-0.009} _{-0.034}	40	39	40		
	6200		40~60		30		9		54	38		24	36		44	42	44	—	
	6801		25~50		21		5		44	29		17	26	^{-0.007} _{-0.028}	34	35	34		
	6901				24		6		48	31		21	30		38	38	38		
Square Flange Type	6001		30~60	12	28		8	2.85	52	36		24	34	^{-0.009} _{-0.034}	42	40	42		
	6201	ZZ (Double-lid type)	40~70		32	^{+0.025} ₀	10		56	40		26	38		46	43	46		
	6802		25~60		24		5		47	32		20	30	^{-0.007} _{-0.028}	37	37	37		
	6902	※VV (Non-contact rubber seal ring)	30~70	15	28	^{+0.021} ₀	7		57	37		25	35		45	45	45		
	6002				32		9		60	40		28	38		48	46	48		
	6202		40~70		35	^{+0.025} ₀	11	3.75	64	44		29	42		52	49	52		
	6903				30	^{+0.021} ₀	7	2.85	60	38		10	27		48	46	48	9.5	5.7
	6003	DD (Contact rubber seal ring)		17	35		10	3.75	66	44		31	42	^{-0.009} _{-0.034}	54	50	54		
	6203		50~70		40		12	3.95	72	50		34	48		60	54	60		
	6804		35~70		32		7		60	40		28	38		48	46	38	29	
Opposite Edge Flange Type	6904		45~70		37		9	3.75	69	47		34	45		56	54	51	24	
	6004			20	42	^{+0.025} ₀	12	3.95	77	54		36	50		64	59	56	32	
	6204		55~80		47		14		81	58		40	54	^{-0.010} _{-0.040}	68	62	59	34	11
	6805				37		7	3.75	69	47		34	45	^{-0.009} _{-0.034}	56	54	51	24	
	6905		35~70		42		9		77	54		36	50		64	59	56	32	
	6005				47		12	3.95	88	58		41	54	^{-0.010} _{-0.040}	72	67	63	36	14
	6205		55~80		52	^{+0.030} ₀	15	4.2	94	64		45	60		78	72	68	39	9.2
	6806				42		7		77	54		36	50	^{-0.009} _{-0.034}	64	59	56	32	11
	6906		35~70		47	^{+0.025} ₀	9	3.95	88	58		41	54		72	67	63	36	6.8
	6006		55~80		55		13		96	66		48	62	^{-0.010} _{-0.040}	80	73	70	40	9.2
	6206				62		16	4.2	104	74		55	70		88	79	77	44	
	6007		55~120		72	^{+0.030} ₀	17		126	88		64	84	^{-0.012} _{-0.047}	105	95	92	51	17.5
	6207			35	72		6		126	88	20	64	84	^{-0.010} _{-0.040}	96	86	80	54	11.2
	6008				68		15	5.2	114	82	13	60	78		102				8.3
	6208		65~120		80		18		134	96		74	92	^{-0.012} _{-0.047}	113	98	56	17.5	11.2
	6010			50	90	^{+0.035} ₀	20	7	147	110		83	106		126	—	104	72	
	6210	ZZ (Double-lid type)	70~120		90		20		147	110		83	106		126				

※ VV(Non-contact rubber seal ring) is not applicable to bearings of model 623,624,605,606.

※ VV(Non-contact rubber seal ring),DD(Contact rubber seal ring), bearing material: steel.

Optional Processing

Code	Do not assemble the bearing and retainer ring
NA	
Technical Specification	Not assembled with bearings and retainers (shipped separately)