

Mounted Bearing ▶ Double bearing guided flange type

Retainer type with L size option



Please order according to the diagram

①~④ Select the type and parameters in the order of for ordering

Model(①Code) — Bearing Model — Seal ring — L — NA

YCAFO

6000

ZZ

L50

NA

Optional Processing




Discounted Price
Quantity 1~9 10~
Price 100% Separate Quotation
Price Excluding Tax (Yen)




CAD 3D

Type			Material		Surface Treatment	
Round Flange Type	Square Flange Type	Opposite Edge Flange Type	Bearing	Bearing Housing	Retaining Ring	Bearing Housing
YCAFO	YCFBO	YCFCO	Steel	S45C	Spring steel	Black Oxide Finish
YCFAP	YCFBP	YCFCP		A2017	SUS304	Electroless Nickel Plating
YCFAT	YCFBT	YCFCT	Stainless Steel	SUS304		Natural Anodizing
YCFBU	YCFBU	YCFBU				—
YCFBU	YCFBU	YCFBU				


■ Bearing accuracy: GB/T 307.10 Grade, Equivalent to JIS B 15140 Grade.




Round Flange Type



Square Flange Type



Opposite Edge Flange Type



Code	Model	Seal Rings	L	S	d	DH7	B	V	H	W	T	dh	D1g7	P.C.D	K	A	F	d1	d2	H1
623	Round Flange Type		20 30	3	10	+0.015	4		33	16	7	7	14	24	27	24		6.5	3.7	3.3
624				5	4	13			35	18		9	17	-0.008 -0.024	26	28	26			
605			25 35	14	5	+0.018 0	5		38	20		10	18	26.5	30	26.5				
625			35 40	10	5	16			40	22		12	20	30	31	30				
606			25 40	5	5	17		2.65	41	23		13	21	31	32	31				
626			35 45	10	6	19		6	44	25		15	24	34	34	34				
698			25 35	5	8	22		7	47	29		18	27	37	36	37				
608			35 45	10	8	24		8	2.85	50	32	20	30	40	37	40				
628			20 30	5	10	19		5	44	25		15	24	34	34	34				
6900			25 40	10	10	22		6	47	29		19	27	37	36	37				
6000			35 50	10	10	26		8	52	34		22	32	42	39	42				
YCAFO			45 55	15	10	30		9	56	38		24	36	46	42	46				
YCFAP			25 35	5		21		5	47	29		17	26	37	36	37				
YCFAT			25 35	5		24		6	50	31		21	30	40	38	40				
YCFBU			35 50	10	12	28		8	2.85	54	36	24	34	44	40	44				
6001			45 55	15		32		10	58	40		26	38	48	43	48				
6201			25 35	5		24		5	50	32		20	30	40	37	40				
6802			35 60	10		28		7	59	37		25	35	47	45	47				
YCFBO			45 65	15		32		9	62	40		28	38	50	46	50				
YCFBP			50 65	15		35		11	3.75	66	44	29	42	54	49	54				
YCFBT			45 55	15		30		7	2.85	60	38	10	27	48	46	48				
YCFBU			50 65	17		35		10	3.75	66	44	31	42	54	50	54				
YCFBQ			60 70	20		40		12	3.95	72	50	34	48	60	54	60				
6804			35 50	10		32		7	62	40		28	38	50	46	44	24			
YCFCO			50 65	15		37		9	72	47		34	45	59	54	54	24			
YCFCP			60 70	20		42		12	3.95	77	54	36	50	64	59	56	32			
YCFCT			65 70	20		47		14	81	58		40	54	68	62	59	34	11	6.8	6.3
6805			35 50	15		37		7	3.75	72	47	34	45	59	54	54	24			
6905			60 80	20		42		9	77	54		36	50	64	59	55	32			
6005			65 85	20		47		12	3.95	88	58	41	54	72	67	63	36	14	9.2	8.3
6205			65 85	20		52		15	4.2	94	64	45	60	78	72	68	39			
6806			35 50	15		42		7	77	54		36	50	64	59	56	32	11	6.8	6.3
6906			60 80	20		47		9	88	58		41	54	72	67	62	36			
6006			70 90	20		55		13	96	66		48	62	80	73	70	40	14	9.2	8.3
6206			70 90	20		62		16	4.2	104	74	55	70	88	79	77	44			
6007			70 90	20		62		14												
6207			70 90	20		72		17	6	126	88	20	64	84	105	95	92	51	17.5	11.2
6008			80 90	25		68		15	5.2	114	82	13	60	78	96	86	80	54	14	9.2
6208			70 90	20		80		18	6	134	96	20	74	92	113	102	98	56	17.5	11.2
6010			80	20		16		16												
6210			100	50		90		20	7	147	110	83	106	126	—	104	72			

※ VV(Non-contact rubber seal ring) is not applicable to bearings of model 623,624,605,606.

※ VV(Non-contact rubber seal ring),DD(Contact rubber seal ring), bearing material: steel.

□ Please note to avoid the retainer ring, refer to the retainer ring size for referenceP851.

Optional Processing

Code	Do not assemble the bearing and retainer ring
NA	
Technical Specification	Not assembled with bearings and retainers (shipped separately)