

Mounted Bearing ▶ Double bearing guided flange type Non-retainer type with L size option



Please order according to the diagram

①~③ Select the type and parameters in the order of for ordering

Model(①Code) —

YCFGO

② Bearing Model —

6801

③ Seal ring —

DD

④ L —

L35

Optional Processing

NA



Discounted Price

Quantity 1~9 10~

Price 100% Separate Quotation


Price Excluding Tax (Yuan)



CAD 2D

Type			Material		Surface Treatment
Round Flange Type	Square Flange Type	Opposite Edge Flange Type	Bearing	Bearing Housing	Bearing Housing
YCFGO	YCFHO	YCFJO	Steel	S45C	Black Oxide Finish
YCFGP	YCFHP	YCFJP		A2017	Electroless Nickel Plating
YCFGT	YCFHT	YCFJT		SUS304	Natural Anodizing
YCFGU	YCFHU	YCFJU	Stainless Steel		
YCFGQ	YCFHQ	YCFJQ			





■ Bearing accuracy: GB/T 307.10 Grade, Equivalent to JIS B 15140 Grade.



Round Flange Type

Square Flange Type

Opposite Edge Flange Type



	Model																		
Code	Bearing Model	Seal Rings	Selection	S	d	D _{H7}	B	H	W	T	dh	D _{1g7}	P.C.D	K	A	F	d ₁	d ₂	H ₁
Round Flange Type	623	ZZ (Double-lid type)	20 30	5	3	10	^{+0.015} ₀	4	33	16	7	7	14	24	27	24	6.5	3.7	3.3
	624				4	13			35	18	9	17	-0.006 -0.024	26	28	26			
	605		25 35	10	5	14		^{+0.018} ₀	5	38	20	10	18	28	30	28	8	4.7	4.3
	625		35 40			16		40	22	12	20	30	31	30					
	606		25 40	5	17		41	23	13	21	-0.007 -0.028	29	32	29					
	626		35 45	10	6	19	^{+0.021} ₀	6	44	25	15	24	34	34	34				
	678		20 30	12	^{+0.018} ₀	3.5	35	18	10	16	-0.006 -0.024	26	28	26					
	698		25 35	5	19	6	44	25	15	24	34	34	34						
	608		35 45	10	8	22	^{+0.021} ₀	7	47	29	18	27	37	36	37				
	628		20 30	5	24	8	50	32	20	30	-0.007 -0.028	40	37	40					
	6700		25 40	10	15	^{+0.018} ₀	4	40	22	12	19	30	31	30					
	6800		35 50	5	19	5	44	25	15	24	34	34	34						
	6900		45 55	10	22	6	47	29	19	27	37	36	37						
	6000		50 65	15	26	8	52	34	22	32	-0.009 -0.034	42	39	42					
	6200		60 70	20	30	9	56	38	24	36	46	42	46						
	YCFGO		70 80	25	34	10	60	40	26	38	50	46	50						
YCFGP	80 90	30	38	11	66	44	28	42	54	49	54								
YCFGT	90 100	35	42	12	72	50	30	45	59	54	54								
YCFGU	100 110	40	46	13	78	54	32	48	62	56	56								
YCFGQ	110 120	45	50	14	84	60	34	50	66	60	60								
Square Flange Type	6201	VV (Non-contact rubber seal ring)	25 35	10	21	4	^{+0.021} ₀	4	47	29	18	26	37	36	37	8	4.7	4.3	
	6802				35 60	24	5	50	32	20	30	-0.007 -0.028	40	37	40				
	6902		45 65	15	28	7	59	37	25	35	47	45	47						
	YCFHO		50 65	20	32	9	62	40	28	38	50	46	50						
	YCFHP		60 70	25	35	11	66	44	29	42	54	49	54						
	YCFHT		70 80	30	38	12	72	50	30	45	59	54	54						
	YCFHU		80 90	35	42	13	78	54	32	48	62	56	56						
	YCFHQ		90 100	40	46	14	84	60	34	50	66	60	60						
	6803		50 65	15	26	8	52	34	22	32	42	39	42						
	6903		60 70	20	30	9	56	38	24	36	46	42	46						
	6003		70 80	25	34	10	60	40	26	38	50	46	50						
	6203		80 90	30	38	11	66	44	28	42	54	49	54						
	YCFJO		90 100	35	42	13	78	54	32	48	62	56	56						
	YCFJP		100 110	40	46	14	84	60	34	50	66	60	60						
	YCFJT		110 120	45	50	15	90	66	36	54	70	62	62						
	YCFJU		120 130	50	54	16	96	72	38	58	74	64	64						
YCFJQ	130 140	55	58	17	102	78	40	60	78	66	66								
Opposite Edge Flange Type	6805	ZZ (Double-lid type)	35 50	15	37	7	^{+0.025} ₀	7	72	47	34	45	59	54	54	11	6.8	6.3	
	6905				42	9	77	54	36	50	64	59	55	32					
	6005		60 80	20	47	12	88	58	41	54	72	67	63	36					
	6205		65 80	25	52	15	94	64	45	60	78	72	68	39					
	6806		35 50	15	42	7	77	54	36	50	64	59	56	32					
	6906		60 80	20	47	9	88	58	41	54	72	67	63	36					
	6006		60 80	20	55	13	96	66	48	62	80	73	70	40					
	6206		70 80	25	62	16	104	74	55	70	88	79	77	44					
	6007		70 90	30	72	17	112	80	58	74	92	81	79	46					
	6207		80 90	35	77	18	117	84	60	78	96	84	80	48					
	6808		90 100	40	80	19	120	88	62	80	100	86	82	50					
	6208		100 110	45	85	20	125	90	64	84	105	95	92	51					
	6010		110 120	50	90	21	130	96	66	86	110	98	94	53					
	6210		120 130	55	95	22	135	100	68	90	115	102	98	54					
	6810		130 140	60	100	23	140	104	70	94	120	106	102	55					
	6210		140 150	65	105	24	145	108	72	96	125	110	106	56					

※ VV(Non-contact rubber seal ring) is not applicable to bearings of model 623,624,605,606.

※ VV(Non-contact rubber seal ring),DD(Contact rubber seal ring), bearing material: steel.

ⓘ Please note to avoid the retainer ring, refer to the retainer ring size for referenceP851.

Optional Processing

Code	Do not assemble the bearing and retainer ring
NA	
Technical Specification	Not assembled with bearings and retainers (shipped separately)