

Pulley for Round Belt ▶ U-Shaped Groove Screw-fixed Type



Please order according to the diagram

①~④ Select the type and parameters in the order of for ordering

Model(①Code)

VUFCH

— ②A

A30

— ③R

R1

— ④ Shaft Hole Specification and Inner Diameter Selection(H/P/N/C)

H5



Discounted Price	
Quantity	Price
1~9	100%
10~	Separate Quotation

Price Excluding Tax (¥/unit)





CAD 2D 3D

Code	Type	Material		Surface Treatment
		National Standard	Equivalent	
VUFCH	U-Shaped Groove Screw-fixed Type	45	S45C	Black Oxide Finish
VUFCN				Electroless Nickel Plating
VUFCV		45	S45C	Natural Anodizing
VUFDH				Black Oxide Finish
VUFDN	With Hub	0Cr18Ni9	SUS304	Electroless Nickel Plating
VUFDU		LF2	A5052	Natural Anodizing
VUFDV				

① If rust prevention is required, stainless steel or electrolytic nickel plating products are preferred.


Shaft Hole Specification




N New JIS Keyway Hole + Threaded Hole
C Old JIS Keyway Hole + Threaded Hole



Without Hub



With Hub



6.3

Model		R	Shaft Hole Specification and Inner Diameter Selection			D ₁	D ₂	T	T ₁	L	V	D	m	Applicable Belt Diameter						
Code	A		Minimum Unit 1		Selection															
			H·P (H7)	N (NewJIS)	C (Old JIS)															
VUFDH VUFDN VUFDU VUFDV	15	1	3~7	—	—	17	13	5	2.5	11	3	12	M3	2						
	20		3~12	8~10		22	18					16								
	30					32	28					20								
	40					42	38					25								
Without Hub VUFCH VUFCH VUFCH VUFCH With Hub VUFDH VUFDN VUFDU VUFDV	20	1.5	3~12	8	—	22	17	10	5	16	3	16	M3	3						
	30		4~12	8~10		32	27					20								
	40					42	37					25								
	45					47	42					30								
	60	4~20	8~20 (8~15)	10	62	57	20	5	25	M4										
	18				8	20	14	16												
	23					25	19	20												
	28	2	4~12	8~10		—	30	24	16	3	20	M3	4							
	30				32		26													
	40				42		36	25												
	45		47	41	30															
	48	4~20	8~20 (8~15)	10	50	44	20	5	25	M4	5									
	60				62	56														
	80				82	76														
	28				4~12	8~10						—	30	23	16	3	20	M3	6	
	40	42	35	25																
	48	50	43	30																
	50	2.5	4~20	8~20 (8~15)	10	52	45	10	5	20	5	25	M4	7						
	60					62	55													
	75					77	70													
80	82					75														
With Hub VUFCH VUFDN VUFDU VUFDV	28	4~12	8~10	—	30	22	10	5	16	3	20	M3	8							
	38				40	32														
	48				50	42														
	50				52	44														
	58	8~20 (8~15)	10	60	52	20	5	25	M4	9										
	60			62	54															
	75			77	69															
	80			82	74															
	95	97	89	15	7.5	27	6	30	M4 (M5)	10										
	100	102	94																	
	50	4~20	8~20								10 12 15	52	42	12	6	24	6	30	M4 (M5)	11
	60											62	52							
	80			82	72															
	100			102	92															
	120	8~20	10 12 15	122	112	15	7.5	27	6	30	M4 (M5)	12								
	60			62	50															
80	82			70																
100	102			90																
120	122	110	142	130	15	7.5	27	6	30	M4 (M5)	13									
140	142	130																		

① Shaft Hole Specification (N) specifications are for hub type dimensions.

※ When the diameter of the shaft hole is 15 or more, the m is the () inside dimension.