

Idler pulley for round belt ▶ Narrow width type • Standard type / External thread type



Please order according to the diagram

①~③ Select the type and parameters in the order of for ordering

Model(①Code) — ②A — ③R
VUQAH — A20 — R1.1



Discounted Price
Quantity 1~9 10~
Price 100% Separate Quotation


Prior Excluding Tax (Yen)

Code	Type	Main Body			External thread			Bearing
		National Standard	Equivalent	Surface Treatment	National Standard	Equivalent	Surface Treatment	
VUQAH	Standard type	45	S45C	Black Oxide Finish	—	—	—	Steel
VUQAN		—	—	Electroless Nickel Plating	—	—	—	—
VUQAV		—	—	Natural Anodizing	—	—	—	—
VUQAU	Narrow width type	0Cr18Ni9	SUS304	—	—	—	—	Stainless Steel
VUQBH		—	—	—	—	—	—	—
VUQBN		—	—	—	—	—	—	—
VUQBV	External thread type	45	S45C	Black Oxide Finish	45	S45C	—	Steel
VUQBU		—	—	Electroless Nickel Plating	—	—	—	—
VUQBU		—	—	Natural Anodizing	—	—	—	—
VUQBU	External thread type	0Cr18Ni9	SUS304	—	0Cr18Ni9	SUS304	—	Stainless Steel
VUQBU		—	—	—	—	—	—	—
VUQBU		—	—	—	—	—	—	—


■ Bearing accuracy: GB/T 307.1 Grade 0
Equivalent: JIS B 154 Grade 0

① If rust prevention is required, stainless steel or electrolytic nickel plating products are preferred.

Standard type



External thread type



- ① Bearings are adhesive type
- ② External threaded pins are riveted.

Model	A	R	F	d	P	D	D ₁	B	Standard bearing	M	G	F ₁	Applicable diameter for round belts
Standard type	(15)	1.1	—	4	11	17	13	4	YHJ 694ZZ	—	—	—	2
	(20)			5	13	21	18	—	YHJ 624ZZ	—	—	—	—
	(30)			4	16	32	28	—	YHJ 625ZZ	—	—	—	—
	(20)	1.6	—	4	13	22	17	—	YHJ 624ZZ	—	—	—	—
	(23)			5	16	25	20	5	YHJ 625ZZ	—	—	—	3
	(30)			5	16	32	27	—	YHJ 625ZZ	—	—	—	—
	(18)	2.1	8	6	11	20	14	—	YHJ 685ZZ	—	—	—	—
	23			15	25	19	—	—	YHJ 696ZZ	—	—	—	—
	28			19	30	24	—	—	YHJ 626ZZ	M6	3	1.0	4
	30			8	19	32	26	—	YHJ 698ZZ	—	4	—	—
External thread type	40	2.6	12	12	24	42	36	6	YKY 6901ZZ	M10	6	1.5	—
	48			6	19	50	44	—	YHJ 626ZZ	—	3	—	—
	28			6	19	30	23	—	YHJ 626ZZ	—	3	—	—
	40	3.1	10	8	24	42	35	8	YHJ 698ZZ	M6	4	1.0	5
	48			8	24	50	43	—	YKY 6901ZZ	—	6	—	—
	50			12	24	52	45	—	YKY 6901ZZ	M10	6	1.5	—
	38	4.1	8	8	24	40	32	10	YHJ 628ZZ	M8	4	1.0	—
	48			8	24	50	42	—	YHJ 628ZZ	—	4	—	—
	50			12	28	52	44	—	YKY 6001ZZ	—	—	—	—
	60	5.1	12	20	37	102	94	9	YKY 6904ZZ	—	—	—	—
	50			12	32	52	42	10	YKY 6201ZZ	M10	6	1.5	8
	60			—	—	62	52	—	—	—	—	—	—
	60			—	—	62	50	—	—	—	—	—	—
	80			20	42	82	70	12	YKY 6004ZZ	—	—	—	10
(140)	—	—	—	—	—	142	130	—	—	—	—	—	—

① Dimensions with () are not suitable for external thread type.