

Leg Leveling Feet ▶ Fixed Adjustable Type • Trumpet Shape • Without Positioning Holes

Medium Load Type



Please order according to the diagram

①~④ Select the type and parameters in the order of for ordering.

Model(①Code) — ②D — ③M — ④L
DABAO — D80 — M12 — L50




Discounted Price

Quantity Price 1~9 10~
 100% Separate Quotation

Price Excluding Tax (Yuan)



CAD 2D 3D



Code	Type	Material	Surface Treatment
DABAO	Without Positioning Holes	S45C	Nickel plating
DABAP		SUS304	Electrolytic Grinding

Features: The product's base is a disc-shaped stamping part, making it more suitable for use in conveyor line equipment.

Model		M	L	S	H	T	V	V ₁	Load Capacity (Kg)	Reference Weight (Kg/pcs)	
Code	D										
DABAO DABAP	40	8	30	14		2	5.5	6.5	350	0.04	
			50							0.05	
			100							0.07	
			10	50	17		7	8		0.08	
				75						0.09	
				100						0.1	
		8	30	14	10		5.5	6.5		0.05	
			50							0.07	
			100							0.08	
			10	50	17	2	7	8	400	0.09	
				75						0.1	
				100						0.11	
		12	50	19			8	10		0.11	
			100							0.15	
			150							0.18	
			10	50	17			7	8		0.08
				100							0.11
				150							0.13
	60	12	50	19		2	8	10	500	0.17	
			100							0.2	
			150							0.21	
			16	50	24			10	13		0.28
				100							0.33
				150							0.36
		12	50	19	14		8	10		0.16	
			100							0.19	
			150							0.23	
			16	50	24		2.5	10	13	700	0.25
				100							0.3
				150							0.39
80	20	50	30			13	16		0.47		
		100							0.5		
		150							0.48		
		24	50	36			16	19		0.52	
			100								
			150								

Load Capacity Test (Test Model: DABAO -D80-M24-L150)

