

Anti-Vibration Leveling Feet ▶ Fixed Adjustable Type • Metal + Rubber Base Type

Medium Load Type



Please order according to the diagram

①~④ Select the type and parameters in the order of for ordering.

Model(①Code) — ②D — ③M — ④L
DADBQ — D40 — M8 — L30




Discounted Price

Quantity 1-9 10-
Price 100% Separate Quotation

Price Excluding Tax (Yuan)



CAD 2D 3D



Code	Type	Material			Surface Treatment	
		Cover	Screw Rod	Bottom	Cover	Screw Rod
DADBQ	Metal + Rubber Base Type	Q235		Rubber	Nickel Plated	

Features of Thickened Rubber Base Type:

- The product's bottom employs thick rubber to enhance shock absorption and anti-slip capabilities.
- The base shell is made of carbon steel, ensuring the product's load-bearing capacity.

Model		M	L	S	H	T	V	V ₁	Vertical Load Capacity (Kg)	Reference Weight (Kg/pcs)
Code	D									
DADBQ	40	8	30	14	16		5.5	5.5	350	0.07
			50							0.08
		10	30	17			7	8		0.09
			50							
			80							0.11
			100							
			50							0.12
			80							
		12	100	19			8	10		0.16
			120							
			150							0.19
		60		10			30	17		2
	50				0.17					
	80				0.18					
	100				0.19					
				50				0.19		
				80					0.22	
	12		100	19	8	10	0.24			
			120					0.25		
			150					0.27		
	20		60	50	20				0.27	
				80						0.3
			16	100	24		10	13		0.33
				120						
				150						0.41
					50					
	80				0.36					
	20			100	30	13	16		0.42	
				120						0.48
		150					0.58			

Load Capacity Test (Test Model: DADBQ-D60-M20-L150)

