

Double-row sprocket ▶ 40/50 Series



Please order according to the diagram

①~④ Select the type and parameters in the order of for ordering

■ 40 Series

Model(①Code)

② Number Teeth

③ Shaft Hole Diameter DH7

ECKCA-40

12

D18



Price Excluding Tax (Yuan)

● Discounted Price

Quantity 1~9 10~
Price 100% Separate Quotation





CAD 2D

Code	Type	Material		Heat Treatment	Surface Treatment
		National Standard	Equivalent		
ECKCA	40 Series	45	S45C	High-frequency both tip	Black Oxide Finish
ECKDA	50 Series				

■ Keyway/Threaded Hole Size

D	Keyway b×t ₁	M
15	5×2.3	6
18~20	6×2.8	
25~30	8×3.3	
35	10×3.3	8
40	12×3.3	



- ① Offset between tooth tip and keyway center is +0.5.
- ② Due to manufacturing tolerances, it is not possible to ensure that the tooth tips and keyways of multiple products will align perfectly.

■ 40 Series

Model		Shaft Hole Diameter			Outer Diameter	Diameter of Reference Circle	Hub		B	P	Weight(kg)
Code	Number Teeth	DH7			Do	Dp	H	L			
ECKCA-40	12	15	18		55	49.07	34				0.33
	13	18	20		59	53.07	38				0.4
	14	18	20		63	57.07	42				0.49
	15	20	25		67	61.08	46				0.57
	16	20	25		71	65.1	50				0.66
	17	25	28	30	76	69.12	54				0.76
	18	25	28	30	80	73.14	59				0.89
	19	25	28	30	84	77.16	63				1
	20	25	28	30	88	81.18	67				1.14
	21	25	28	30	92	85.21	71				1.23

■ 50 Series

Model		Shaft Hole Diameter			Outer Diameter	Diameter of Reference Circle	Hub		B	P	Weight(kg)
Code	Number Teeth	DH7			Do	Dp	H	L			
ECKDA-50	12	18	20		69	61.34	43				0.63
	13	20	25	28	74	66.34	48				0.75
	14	20	25	28	79	71.34	53				0.9
	15	20	25	28	84	76.35	58				1.04
	16	25	28	30	89	81.37	63				1.22
	17	25	28	30	94	86.39	68				1.41
	18	25	28	30	100	91.42	73				1.61
	19	25	28	30	105	96.45	79				1.8
	20	25	28	30	110	101.48	84				1.95
	21	28	30	35	115	106.51	89				2.27