

# Cross Recessed Pan Head Screws / Cross Recessed Truss Head Screws



Please order according to the diagram

①~③ Select the-Type and parameters in the order of for ordering

② Cross Recessed Low Profile Pan Head Screws

Model(①Code) - ②M - ③L  
UOQUS - M2.5 - L6

③ Cross Recessed Truss Head Screws

Model(①Code) - ②M - ③L  
UORWQ - M2 - L6



| Discounted Price |      |                    |
|------------------|------|--------------------|
| Quantity         | 1~9  | 10~                |
| Price            | 100% | Separate Quotation |


Price Excluding Tax (¥/unit)

## ② Cross Recessed Pan Head Screws



CAD 2D

| Code  | Type                                       | Material                      |            | Surface Treatment | Applicable standards |
|-------|--------------------------------------------|-------------------------------|------------|-------------------|----------------------|
|       |                                            | International                 | Equivalent |                   |                      |
| UOQUS | Cross Recessed Pan Head Screws             | Carbon Steel for Cold Heading |            | Zinc Plated       | B/T 818-2000         |
| UOQUQ |                                            |                               |            |                   | ISO 7045-1994        |
| UOQVQ | Cross Recessed Low Profile Pan Head Screws | 0Cr18Ni9                      | SUS304     | —                 | GB/T 823-2016        |



## ③ Cross Recessed Pan Head Screws

| Model           |     |   |   |   |    |    |    |    |    |    |    |    |    |    |    |    | P            | D   | K   |
|-----------------|-----|---|---|---|----|----|----|----|----|----|----|----|----|----|----|----|--------------|-----|-----|
| Code            | M   | L |   |   |    |    |    |    |    |    |    |    |    |    |    |    | Thread pitch |     |     |
| (SWCH)<br>UOQUS | 2,5 | 4 | 6 | 8 | 10 | 12 |    |    |    |    |    |    |    |    |    |    | 0.45         | 5   | 2.1 |
|                 | 3   | 4 | 6 | 8 | 10 | 12 | 16 | 18 | 20 | 25 | 30 | 35 | 40 |    |    |    | 0.5          | 5.6 | 2.4 |
|                 | 4   |   | 5 | 6 | 8  | 10 | 12 | 14 | 16 | 20 | 25 | 30 |    |    |    |    | 0.7          | 8   | 3.1 |
|                 | 5   |   |   | 8 | 10 | 12 | 14 | 16 | 20 | 25 | 30 | 35 | 40 |    |    |    | 0.8          | 9.5 | 3.7 |
|                 | 6   |   |   | 8 | 10 | 12 | 14 | 16 | 20 | 25 | 30 | 35 | 40 | 45 | 50 | 65 | 70           | 1.0 | 12  |

| Model             |     |   |   |   |   |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |      | P            | D   | K   |     |      |     |     |     |     |
|-------------------|-----|---|---|---|---|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|------|--------------|-----|-----|-----|------|-----|-----|-----|-----|
| Code              | M   | L |   |   |   |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |      | Thread pitch |     |     |     |      |     |     |     |     |
| (SUS304)<br>UOQUQ | 1.6 | 2 | 3 | 4 | 5 | 6  | 8  | 10 | 12 | 14 | 16 |    |    |    |    |    |    |    |    |    |    |    |    |    | 0.35 | 3.2          | 1.3 |     |     |      |     |     |     |     |
|                   | 2   | 2 | 3 | 4 | 5 | 6  | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 25 |    |    |    |    |    |    |    |    |    |    | 0.4  | 4            | 1.6 |     |     |      |     |     |     |     |
|                   | 2.5 | 3 | 4 | 5 | 6 | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 25 | 30 |    |    |    |    |    |    |    |    |    |    | 0.45 | 5            | 2.1 |     |     |      |     |     |     |     |
|                   | 3   | 4 | 5 | 6 | 8 | 10 | 12 | 14 | 16 | 18 | 20 | 25 | 30 | 35 | 40 | 45 | 50 |    |    |    |    |    |    |    | 0.5  | 5.6          | 2.4 |     |     |      |     |     |     |     |
|                   | 3.5 |   |   |   |   |    |    | 6  | 8  | 10 | 12 | 14 | 16 |    |    |    |    | 20 | 25 | 35 |    |    |    |    |      |              |     | 0.6 | 7   | 2.6  |     |     |     |     |
|                   | 4   |   |   |   |   |    |    | 6  | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | 65 | 70   | 75           | 80  |     |     |      | 0.7 | 8   | 3.1 |     |
|                   | 5   |   |   |   |   |    |    | 6  | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | 65 | 70   | 75           | 80  | 85  | 90  | 95   | 100 | 0.8 | 9.5 | 3.7 |
|                   | 6   |   |   |   |   |    |    | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | 65 | 70 | 75   | 80           | 85  | 90  | 95  | 100  | 1.0 | 12  | 4.6 |     |
|                   | 8   |   |   |   |   |    |    | 10 | 12 | 14 | 16 | 18 | 20 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | 65 | 70 | 75 | 80   | 85           | 90  | 95  | 100 | 1.25 | 16  | 6   |     |     |
|                   | 10  |   |   |   |   |    |    | 12 | 14 | 16 | 18 | 20 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | 65 | 70 | 75 | 80 | 85   | 90           | 95  | 100 | 1.5 | 20   | 7.5 |     |     |     |

## ③ Cross Recessed Low Profile Pan Head Screws


| Model             |     | L  |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |     |      | P            | D    | K   |      |     |      |
|-------------------|-----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|-----|------|--------------|------|-----|------|-----|------|
| Code              | M   |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |     |      | Thread pitch |      |     |      |     |      |
| (SUS304)<br>UOQVQ | 2   | 3  | 4  | 5  | 6  | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 |    |    |    |    |    |    |    |    |    |     | 0.4  | 3.5          | 1.4  |     |      |     |      |
|                   | 2.5 | 3  | 4  | 5  | 6  | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 | 30 |    |    |    |    |    |    |    |    |     |      | 0.45         | 4.5  | 1.8 |      |     |      |
|                   | 3   | 4  | 5  | 6  | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 | 30 | 35 | 40 | 45 | 50 |    |    |    |    |    |     |      |              |      |     | 0.5  | 5.5 | 2.15 |
|                   | 4   | 5  | 6  | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | 65 | 70 | 75 | 80 |     |      |              |      |     | 0.7  | 7   | 2.75 |
|                   | 5   | 6  | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | 65 | 70 | 75 | 80 | 85 | 90  | 95   | 100          | 0.8  | 9   | 3.45 |     |      |
|                   | 6   | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | 65 | 70 | 75 | 80 | 85 | 90 | 95  | 100  | 1.0          | 10.5 | 4.1 |      |     |      |
|                   | 8   | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | 65 | 70 | 75 | 80 | 85 | 90 | 95 | 100 | 1.25 | 14           | 5.4  |     |      |     |      |

## ③ Cross Recessed Truss Head Screws



CAD 2D

| Code  | Type                             | Material      |            | Surface Treatment | Applicable standards |
|-------|----------------------------------|---------------|------------|-------------------|----------------------|
|       |                                  | International | Equivalent |                   |                      |
| UORWQ | Cross Recessed Truss Head Screws | 0Cr18Ni9      | SUS304     | —                 | JIS B 1111-1996      |



| Model |     |   |   |   |   |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |      | P            | D    | K     |      |      |      |      |      |
|-------|-----|---|---|---|---|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|------|--------------|------|-------|------|------|------|------|------|
| Code  | M   | L |   |   |   |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |      | Thread pitch |      | (max) |      |      |      |      |      |
| UORWQ | 2   | 3 | 4 | 5 | 6 | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 |    |    |    |    |    |    |    |    |    |    |    | 0.4  | 4.5          | 1.3  |       |      |      |      |      |      |
|       | 2.5 | 3 | 4 | 5 | 6 | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 | 30 |    |    |    |    |    |    |    |    |    |    | 0.45 | 5.7          | 1.6  |       |      |      |      |      |      |
|       | 3   | 4 | 5 | 6 | 8 | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 | 30 | 35 | 40 | 45 | 50 |    |    |    |    |    |    |    | 0.5  | 6.9          | 2.05 |       |      |      |      |      |      |
|       | 4   | 4 | 5 | 6 | 8 | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | 65 | 70 | 75 | 80 |    |      |              |      |       | 0.7  | 9.4  | 2.65 |      |      |
|       | 5   |   |   |   |   |    | 6  | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | 65 | 70 | 75   | 80           | 85   | 90    | 95   | 100  | 0.8  | 11.8 | 3.25 |
|       | 6   |   |   |   |   |    | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | 65 | 70 | 75 | 80   | 85           | 90   | 95    | 100  | 1.0  | 14   | 3.9  |      |
|       | 8   |   |   |   |   |    | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | 65 | 70 | 75 | 80 | 85   | 90           | 95   | 100   | 1.25 | 17.8 | 5    |      |      |