

# Cross Recessed Pan Head Screws / Cross Recessed Truss Head Screws



Please order according to the diagram

①~③ Select the-Type and parameters in the order of for ordering

② Cross Recessed Low Profile Pan Head Screws

Model(①Code) - ②M - ③L  
UOQUS - M2.5 - L6

③ Cross Recessed Truss Head Screws

Model(①Code) - ②M - ③L  
UORWQ - M2 - L6




Discounted Price

Quantity 1~9 10~  
Price 100% Separate Quotation

Price Excluding Tax (Yuan)

## ② Cross Recessed Pan Head Screws

| Code                    | Type                                       | Material                      |            | Surface Treatment | Applicable standards          |
|-------------------------|--------------------------------------------|-------------------------------|------------|-------------------|-------------------------------|
|                         |                                            | International                 | Equivalent |                   |                               |
| UOQUS<br>UOQUQ<br>UOQVQ | Cross Recessed Pan Head Screws             | Carbon Steel for Cold Heading |            | Zinc Plated       | B/T 818-2000<br>ISO 7045-1994 |
|                         | Cross Recessed Low Profile Pan Head Screws | 0Cr18Ni9                      | SUS304     | —                 | GB/T 823-2016                 |



## ③ Cross Recessed Pan Head Screws

| Model           |     |   |   |   |    |    |    |    |    |    |    |    |    |    |    | P            | D   | K   |
|-----------------|-----|---|---|---|----|----|----|----|----|----|----|----|----|----|----|--------------|-----|-----|
| Code            | M   | L |   |   |    |    |    |    |    |    |    |    |    |    |    | Thread pitch |     |     |
| (SWCH)<br>UOQUS | 2.5 | 4 | 6 | 8 | 10 | 12 |    |    |    |    |    |    |    |    |    | 0.45         | 5   | 2.1 |
|                 | 3   | 4 | 6 | 8 | 10 | 12 | 16 | 18 | 20 | 25 | 30 | 35 | 40 |    |    | 0.5          | 5.6 | 2.4 |
|                 | 4   |   | 5 | 6 | 8  | 10 | 12 | 14 | 16 | 20 | 25 | 30 |    |    |    | 0.7          | 8   | 3.1 |
|                 | 5   |   |   |   | 8  | 10 | 12 | 14 | 16 | 20 | 25 | 30 | 35 | 40 |    | 0.8          | 9.5 | 3.7 |
|                 | 6   |   |   |   | 8  | 10 | 12 | 14 | 16 | 20 | 25 | 30 | 35 | 40 | 45 | 50           | 65  | 70  |


| Model             |     |   |   |   |   |   |    |    |    |    |    |    |    |    |    | P            | D    | K   |     |    |     |     |     |    |    |     |     |     |      |     |     |     |
|-------------------|-----|---|---|---|---|---|----|----|----|----|----|----|----|----|----|--------------|------|-----|-----|----|-----|-----|-----|----|----|-----|-----|-----|------|-----|-----|-----|
| Code              | M   | L |   |   |   |   |    |    |    |    |    |    |    |    |    | Thread pitch |      |     |     |    |     |     |     |    |    |     |     |     |      |     |     |     |
| (SUS304)<br>UOQUQ | 1.6 | 2 | 3 | 4 | 5 | 6 | 8  | 10 | 12 | 14 | 16 |    |    |    |    |              | 0.35 | 3.2 | 1.3 |    |     |     |     |    |    |     |     |     |      |     |     |     |
|                   | 2   |   | 2 | 3 | 4 | 5 | 6  | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 25 |              | 0.4  | 4   | 1.6 |    |     |     |     |    |    |     |     |     |      |     |     |     |
|                   | 2.5 |   |   | 3 | 4 | 5 | 6  | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 25 | 30           | 0.45 | 5   | 2.1 |    |     |     |     |    |    |     |     |     |      |     |     |     |
|                   | 3   |   |   |   | 4 | 5 | 6  | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 25 | 30           | 35   | 40  | 45  | 50 | 0.5 | 5.6 | 2.4 |    |    |     |     |     |      |     |     |     |
|                   | 3.5 |   |   |   |   | 6 | 8  | 10 | 12 | 14 | 16 |    | 20 | 25 | 35 |              | 0.6  | 7   | 2.6 |    |     |     |     |    |    |     |     |     |      |     |     |     |
|                   | 4   |   |   |   |   | 6 | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 25 | 30 | 35           | 40   | 45  | 50  | 55 | 60  | 65  | 70  | 75 | 80 | 0.7 | 8   | 3.1 |      |     |     |     |
|                   | 5   |   |   |   |   | 6 | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 25 | 30 | 35           | 40   | 45  | 50  | 55 | 60  | 65  | 70  | 75 | 80 | 85  | 90  | 95  | 100  | 0.8 | 9.5 | 3.7 |
|                   | 6   |   |   |   |   | 8 | 10 | 12 | 14 | 16 | 18 | 20 | 25 | 30 | 35 | 40           | 45   | 50  | 55  | 60 | 65  | 70  | 75  | 80 | 85 | 90  | 95  | 100 | 1.0  | 12  | 4.6 |     |
|                   | 8   |   |   |   |   |   | 10 | 12 | 14 | 16 | 18 | 20 | 25 | 30 | 35 | 40           | 45   | 50  | 55  | 60 | 65  | 70  | 75  | 80 | 85 | 90  | 95  | 100 | 1.25 | 16  | 6   |     |
| 10                |     |   |   |   |   |   | 12 | 14 | 16 | 18 | 20 | 25 | 30 | 35 | 40 | 45           | 50   | 55  | 60  | 65 | 70  | 75  | 80  | 85 | 90 | 95  | 100 | 1.5 | 20   | 7.5 |     |     |

## ③ Cross Recessed Low Profile Pan Head Screws

| Model             |     |   |   |   |   |   |    |    |    |    |    |    |    |    |    | P            | D   | K   |    |     |     |      |    |    |    |     |    |      |     |      |      |      |
|-------------------|-----|---|---|---|---|---|----|----|----|----|----|----|----|----|----|--------------|-----|-----|----|-----|-----|------|----|----|----|-----|----|------|-----|------|------|------|
| Code              | M   | L |   |   |   |   |    |    |    |    |    |    |    |    |    | Thread pitch |     |     |    |     |     |      |    |    |    |     |    |      |     |      |      |      |
| (SUS304)<br>UOQVQ | 2   | 3 | 4 | 5 | 6 | 8 | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 |    | 0.4          | 3.5 | 1.4 |    |     |     |      |    |    |    |     |    |      |     |      |      |      |
|                   | 2.5 | 3 | 4 | 5 | 6 | 8 | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 | 30 | 0.45         | 4.5 | 1.8 |    |     |     |      |    |    |    |     |    |      |     |      |      |      |
|                   | 3   |   | 4 | 5 | 6 | 8 | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 | 30 | 35           | 40  | 45  | 50 | 0.5 | 5.5 | 2.15 |    |    |    |     |    |      |     |      |      |      |
|                   | 4   |   |   | 5 | 6 | 8 | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 | 30 | 35           | 40  | 45  | 50 | 55  | 60  | 65   | 70 | 75 | 80 | 0.7 | 7  | 2.75 |     |      |      |      |
|                   | 5   |   |   |   | 6 | 8 | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 | 30 | 35           | 40  | 45  | 50 | 55  | 60  | 65   | 70 | 75 | 80 | 85  | 90 | 95   | 100 | 0.8  | 9    | 3.45 |
|                   | 6   |   |   |   |   | 8 | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 | 30 | 35           | 40  | 45  | 50 | 55  | 60  | 65   | 70 | 75 | 80 | 85  | 90 | 95   | 100 | 1.0  | 10.5 | 4.1  |
|                   | 8   |   |   |   |   |   | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 | 30 | 35           | 40  | 45  | 50 | 55  | 60  | 65   | 70 | 75 | 80 | 85  | 90 | 95   | 100 | 1.25 | 14   | 5.4  |

## ③ Cross Recessed Truss Head Screws

| Code  | Type                             | Material      |            | Surface Treatment | Applicable standards |
|-------|----------------------------------|---------------|------------|-------------------|----------------------|
|       |                                  | International | Equivalent |                   |                      |
| UORWQ | Cross Recessed Truss Head Screws | 0Cr18Ni9      | SUS304     | —                 | JIS B 1111-1996      |



| Model |     |   |   |   |   |    |    |    |    |    |    |    |    |    |    |    | P            | D   | K     |     |      |    |    |    |     |     |      |    |     |      |      |      |
|-------|-----|---|---|---|---|----|----|----|----|----|----|----|----|----|----|----|--------------|-----|-------|-----|------|----|----|----|-----|-----|------|----|-----|------|------|------|
| Code  | M   | L |   |   |   |    |    |    |    |    |    |    |    |    |    |    | Thread pitch |     | (max) |     |      |    |    |    |     |     |      |    |     |      |      |      |
| UORWQ | 2   | 3 | 4 | 5 | 6 | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 |    |    | 0.4          | 4.5 | 1.3   |     |      |    |    |    |     |     |      |    |     |      |      |      |
|       | 2.5 | 3 | 4 | 5 | 6 | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 | 30 |    | 0.45         | 5.7 | 1.6   |     |      |    |    |    |     |     |      |    |     |      |      |      |
|       | 3   | 4 | 5 | 6 | 8 | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 | 30 | 35 | 40 | 45           | 50  | 0.5   | 6.9 | 2.05 |    |    |    |     |     |      |    |     |      |      |      |
|       | 4   | 4 | 5 | 6 | 8 | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 | 30 | 35 | 40 | 45           | 50  | 55    | 60  | 65   | 70 | 75 | 80 | 0.7 | 9.4 | 2.65 |    |     |      |      |      |
|       | 5   |   |   |   | 6 | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 | 30 | 35 | 40           | 45  | 50    | 55  | 60   | 65 | 70 | 75 | 80  | 85  | 90   | 95 | 100 | 0.8  | 11.8 | 3.25 |
|       | 6   |   |   |   |   | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 | 30 | 35 | 40           | 45  | 50    | 55  | 60   | 65 | 70 | 75 | 80  | 85  | 90   | 95 | 100 | 1.0  | 14   | 3.9  |
|       | 8   |   |   |   |   |    | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 | 30 | 35 | 40           | 45  | 50    | 55  | 60   | 65 | 70 | 75 | 80  | 85  | 90   | 95 | 100 | 1.25 | 17.8 | 5    |