

Cross Recessed Countersunk Head Screws



Please order according to the diagram

1~3 Select the-Type and parameters in the order of for ordering

Carbon steel(SWCH Equivalent)

Model(1Code) - 2M - 3L
UOSXS - M3 - L6

Stainless Steel(SUS304 Equivalent)

Model(1Code) - 2M - 3L
UOSXQ - M2 - L4



Discounted Price


Quantity	1~9	10~
Price	100%	Separate Quotation

Price Excluding Tax (Yuan)



Applicable Standards for This Product : GB/T 819-1985
 ISO 7046-1-1994
 JIS B 1111-1996

Code	Type	Material		Surface Treatment
		International	Equivalent	
UOSXS	Cross Recessed	Carbon Steel for Cold Heading	SWCH	Zinc Plated
UOSXQ	Countersunk Head Screws	0Cr18Ni9	SUS304	—



Carbon steel(SWCH Equivalent)

Model		L														P	D	K				
Code	M															Thread pitch						
UOSXS	2.5	6	8	10	12	14	16	18	20							0.45	4.7	1.5				
	3	4	5	6	8	10	12	14	16	18	20	25	30	35	40	0.5	5.5	1.65				
	4			6	8	10	12	14	16	18	20	25	30	35	40	45	50	0.7	8.4	2.7		
	5			6	8	10	12	14	16	18	20	25	30	35	40	45	50	55	60	0.8	9.3	2.7
	6			8	10	12	14	16	18	20	25	30	35	40	45	50	55	60	1.0	11.3	3.3	
	8			10	12			16	20	25	30	35	40	45	50	55	60	1.25	15.8	4.65		
10					16	20	25	30	35	40	45	50	55	60	1.5	18.3	5					

Stainless Steel (SUS304 Equivalent)

Model		L														P	D	K												
Code	M															Thread pitch														
UOSXQ	1.6	3	4	5	6	8	10	12	14	16	18	20	25							0.35	3	1								
	2	3	4	5	6	8	10	12	14	16									0.4	3.8	1.2									
	2.5	4	5	6	8	10	12	14	16	18	20	25	30							0.45	4.7	1.5								
	3	4	5	6	8	10	12	14	16	18	20	25	30	35	40	45	50	0.5	5.5	1.65										
	4			6	8	10	12	14	16	18	20	25	30	35	40	45	50	55	60	65	70	75	80	0.7	8.4	2.7				
	5			6	8	10	12	14	16	18	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100	0.8	9.3	2.7
	6			8	10	12	14	16	18	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100	1.0	11.3	3.3	
	8			10	12	14	16	18	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100	1.25	15.8	4.65		
	10					16	18	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100	1.5	18.3	5			