

O-Ring ▶ P Series



Please order according to the diagram

①~② Select the type and parameters in the order of for ordering.

③ JIS B 2401

Model(①Code)

CURPA

④ Specification

32




Price Excluding Tax (Year)

Discounted Price



Quantity 1~9 10~

Price 100% Separate Quotation




CAD 2D ED



CURPA/PB/PC/PD
CURPE/PF/PG



① Cross-Section Enlarged View



CURPH



□ P Series O-Ring (JIS B 2401)

Model	Code	Specification	Nominal Number	d2	Dimension	CURPA	CURPB	CURPC	CURPD	CURPE	CURPF	CURPG	d1	Mating Dimensions	d1	D
3	P3			2.8									3	6		
4	P4			3.8	±0.13	±0.20	±0.15						4	7		
5	P5			4.8									5	8		
6	P6			5.8	±0.14	±0.21	±0.17						6	9		
7	P7			6.8	±0.15	±0.23	±0.18						7	10		
8	P8			7.8									8	11		
9	P9			8.8									9	12		
10	P10			9.8	±0.16	±0.24	±0.19						10	13		
10A	P10A			9.8									10	14		
11	P11			10.8	±0.17	±0.26	±0.20						11	15		
11.2	P11.2			11.0									11.2	15.2		
12	P12			11.8									12	16		
12.5	P12.5			12.3	±0.18	±0.27	±0.21						12.5	16.5		
14	P14			13.8									14	18		
15	P15			14.8	±0.19	±0.29	±0.23						15	19		
16	P16			15.8									16	20		
18	P18			17.8	±0.20	±0.30	±0.24						18	22		
20	P20			19.8	±0.21	±0.32	±0.25						20	24		
21	P21			20.8	±0.22	±0.33	±0.26						21	25		
22	P22			21.8									22	26		
22A	P22A			21.7	±0.23	±0.35	±0.27						22	28		
22.4	P22.4			22.1									22.4	28.4		
24	P24			23.7									24	30		
25	P25			24.7	±0.24	±0.36	±0.29						25	31		
25.5	P25.5			25.2									25.5	31.5		
26	P26			25.7	±0.25	±0.38	±0.30						26	32		
28	P28			27.7	±0.27	±0.41	±0.32						28	34		
29	P29			28.7									29	35		
29.5	P29.5			29.2	±0.28	±0.42	±0.33						29.5	35.5		
30	P30			29.7									30	36		
31	P31			30.7	±0.29	±0.44	±0.35						31	37		
31.5	P31.5			31.2	±0.30	±0.45	±0.36						31.5	37.5		
32	P32			31.7									32	38		
34	P34			33.7	±0.32	±0.48	±0.38						34	40		
35	P35			34.7									35	41		
35.5	P35.5			35.2	±0.33	±0.50	±0.39						35.5	41.5		
36	P36			35.7									36	42		
38	P38			37.7									38	44		
39	P39			38.7	±0.36	±0.54	±0.43						39	45		
40	P40			39.7									40	46		
41	P41			40.7	±0.37	±0.56	±0.44						41	47		
42	P42			41.7	±0.38	±0.57	±0.47						42	48		
44	P44			43.7	±0.40	±0.60	±0.48						44	50		
45	P45			44.7									45	51		
46	P46			45.7	±0.41	±0.62	±0.49						46	52		
48	P48			47.7	±0.43	±0.65	±0.51						48	54		
50	P50			49.7	±0.44	±0.66	±0.53						50	56		

□ P Series O-Ring (JIS B 2401)

Model	Code	Specification	Nominal Number	d2	Dimension	CURPA	CURPB	CURPC	CURPD	CURPE	CURPF	CURPG	d1	Mating Dimensions	d1	D
50A	P50A			49.7	±0.44	±0.66	±0.53						50	60		
52	P52			51.6	±0.46	±0.69	±0.55						52	62		
53	P53			52.6	±0.47	±0.71	±0.56						53	63		
55	P55			54.6	±0.48	±0.72	±0.57						55	65		
56	P56			55.6	±0.49	±0.74	±0.59						56	66		
58	P58			57.6	±0.51	±0.77	±0.61						58	68		
60	P60			59.6	±0.52	±0.78	±0.62						60	70		
62	P62			61.6	±0.54	±0.81	±0.65						62	72		
63	P63			62.6	±0.55	±0.83	±0.66						63	73		
65	P65			64.6	±0.56	±0.84	±0.67						65	75		
67	P67			66.6	±0.58	±0.87	±0.69						67	77		
70	P70			69.6	±0.60	±0.90	±0.72						70	80		
71	P71			70.6	±0.61	±0.92	±0.73						71	81		
75	P75			74.6	±0.64	±0.96	±0.77						75	85		
80	P80			79.6	±0.68	±1.02	±0.81						80	90		

□ P Series O-Ring, Bevel (JIS B 2407)

Model	Code	Specification	Nominal Number	d2	d1	D	c
15	P15			15	19		
16	P16			16	20		
18	P18			18	22		
20	P20			20	24		
21	P21			21	25		
22	P22			22	26		
22A	P22A			22	28		
24	P24			24	30		
25	P25			25	31		
26	P26			26	32		
28	P28			28	34		
30	P30			30	36		
32	P32			32	38		
34	P34			34	40		
38	P38			38	44		
40	P40			40	46		
42	P42			42	48		
48	P48			48	54		
50	P50			50	56		