

Gland Packing for Holes



Please order according to the diagram

①~③ Select the type and parameters in the order of for ordering.

Model(●Code)

CVGGL

② Specification

02




Price Excluding Tax (Year)

● Discounted Price

Quantity 1~9 10~



Price 100% Separate Quotation



CAD 2D 3D

Code	Material		Color	Application	Operating Conditions				Service Medium
	Wear-Resistant Ring	O-Ring			Pressure	Speed	Frequency	Wide range of operating temperatures	
CVGGL	PTFE + Bronze	Nitrile Rubber	Brown	Two-Way Reciprocating Seal for Holes	≤60MPa	≤15m/s	≤5Hz	-30~110°C	Mineral-Based Hydraulic Oil, Fire-Resistant Fluid, Biodegradable Hydraulic Oil, Water

● Installation Legend



Seal ring

33

Model		Product Dimensions				Installation Dimensions						
Code	Specification	D	d	d1	H	d2	D1	L	r	S	Radial Clearance(max)	
				O-Ring		Shaft Diameter	Groove Bottom Diameter	Groove Width	(max)	<10MPa	<20MPa	<40MPa
CVGGL	01	30.3	26.84			30	22.5					
	02	32.3	28.84			32	24.5					
	03	35.3	31.84	2.62	2.95	35	27.5	3.2	0.6			0.15
	04	36.3	32.84			36	28.5					
	05	38.3	34.84			38	30.5					
	06	40.3	34.78			40	29					
	07	42.3	36.78			42	31					
	08	45.3	39.78			45	34					
	09	48.3	42.78			48	37					
	10	50.3	44.78			50	39					
	11	51.2	45.68			50.8	39.8					
	12	52.4	46.88			52	41			0.4	0.25	
	13	53.4	47.88			53	42					
	14	55.4	49.88			55	44					
	15	57.4	51.88	3.53	3.95	57	46	4.2	1			0.2
	16	58.4	52.88			58	47					
	17	60.4	54.88			60	49					
	18	62.4	56.88			62	51					
	19	63.4	57.88			63	52					
	20	65.4	59.88			65	54					
	21	68.4	62.88			68	57					
	22	70.4	64.88			70	59					
	23	75.4	69.88			75	64					
	24	80.4	73.22			80	64.5					
	25	82.9	75.72			82.5	67					
	26	85.4	78.22			85	69.5					
	27	90.4	83.22	5.33	6	90	74.5	6.3	1.3	0.5	0.3	0.2
	28	95.4	88.22			95	79.5					
	29	100.4	93.22			100	84.5					
	30	102	94.82			101.6	86.1					
	31	105.4	98.22			105	89.5					
Code	Specification	D	d	d1	H	d2	D1	L	r	S	Radial Clearance(max)	
				O-Ring		Shaft Diameter	Groove Bottom Diameter	Groove Width	(max)	<10MPa	<20MPa	<40MPa
CVGGL	32	108.4	101.22			108	92.5					
	33	110.4	103.22			110	94.5					
	34	115.4	108.22			115	99.5					
	35	120.4	113.22	5.33	6	120	104.5	6.3	1.3	0.5	0.3	0.2
	36	125.5	118.32			125	109.5					
	37	127.5	120.32			127	111.5					
	38	130.5	123.32			130	114.5					
	39	135.5	125.5			135	114					
	40	140.5	130.5			140	119					
	41	145.5	135.5			145	124					
	42	150.5	140.5			150	129					
	43	155.5	145.5			155	134					
	44	160.5	150.5			160	139					
	45	165.5	155.5			165	144					
	46	170.5	160.5			170	149					
	47	175.5	165.5			175	154					
	48	180.5	170.5			180	159					
	49	190.8	180.8			190	169					
	50	200.8	190.8			200	179					
	51	205.8	195.8			205	184					
	52	210.8	200.8			210	189					
	53	215.8	205.8			215	194					
	54	220.8	210.8			220	199					
	55	230.8	220.8			230	209					
	56	240.8	230.8			240	219					
	57	250.8	240.8			250	229					
	58	254.8	244.8			254	233					
	59	260.8	250.8			260	239					
	60	265.8	255.8			265	244					
	61	268.8	258.8			268	247					
	62	270.8	260.8			270	249					