

Floating Joint ▶ External Thread Type

Simplified Connection Type



Please order according to the diagram

①~④ Select the type and parameters in the order of for ordering.

Model(①Code) - ②M - ③Thread pitch - ④L

DQCAG - M3 - 0.5 - L4



Discounted Price


Quantity 1~9 10~
Price 100% (Separate Quotation)

Price Excluding Tax (Yuan)

T-Dimension Fixed Type



CAD 2D/3D



Code	Type	Material		Surface Treatment	Surface hardness
		International	Equivalent		
DQCAG	External Thread Type T-Dimension Fixed Type	45	S45C	Hard Chromium Plating	750HV~

Model		Thread pitch	L	T	t	D	S	e	E	V	R
Code	M										
DQCAG	3	0.5	4	4		4	6	6.9	8	6	
	4	0.7	4	5	3	6	10	11.5	11	9	1
	5	0.8	4 5			8	14	16.2	13	11	
	6	1.0	4 5 6	6		10	17	19.6	19	17	
	8	1.25	5 6 8	8		12	20	24	20	18	1.5
	10	1.5	6 8	9	4	13	24	24	21	21	
	16	2.0	8 12	12		21	30	40	37	37	2
	20	2.5	12 15	15	5	25	34.6	50	46	46	



Please order according to the diagram

①~⑤ Select the type and parameters in the order of for ordering.

Model(①Code) - ②M - ③Thread pitch - ④L - ⑤T

DQDAG - M6 - 1.0 - L5 - T5



Discounted Price


Quantity 1~9 10~
Price 100% (Separate Quotation)

Price Excluding Tax (Yuan)

T-Dimension Specified Type



CAD 2D/3D



Code	Type	Material		Surface Treatment	Surface hardness
		International	Equivalent		
DQDAG	External Thread Type T-Dimension Specified Type	45	S45C	Hard Chromium Plating	750HV~

Model		Thread pitch	L	T Minimum Unit 1	t	D	S	e	E	V	R
Code	M										
DQDAG	6	1.0	4 5		3	7	10	11.5	19	17	
	8	1.25	5 6 8 12	4~30		10	14	16.2	20	18	1.5
	10	1.5	6 8 9 12		4	13	17	19.6	24	21	2