

Floating Joint ▶ Internal Thread Type Simplified Connection Type



Please order according to the diagram

①~④ Select the type and parameters in the order of for ordering.

Model(①Code) — ②M — ③Thread pitch — ④L
DQEBG — M3 — 0.5 — L4



Discounted Price
Quantity 1~9 10~
Price 100% Separate Quotation
Price Excluding Tax (Yuan)

■ T-Dimension Fixed Type

Code	Type		Material		Surface Treatment	Surface hardness
	Internal Thread Type	T-Dimension Fixed Type	International	Equivalent		
DQEBG			45	S45C	Hard Chromium Plating	750HV~

Model													T	t	D	S	e					
Code	M	Thread pitch	L																			
DQEBG	3	0.5	2	3	4	5	6					5	3	6	8	9.2						
	4	0.7	2	3	4	5	6	8						6	7	10	11.5					
	5	0.8	3	4	5	6	8	9	10					7	8	12	13.9					
	6	1.0	3	4	5	6	8	9	10	12					8			10	14	16.2		
	8	1.0	4	5	6	8	9	10	12	13	15	16					9			13	17	19.6
		1.25	4	5	6	8	9	10	12	13	15	16										
	10	1.25	4	5	6	8	9	10	12	13	15	16	19	20	11	4	16	21	24.2			
		1.5	4	5	6	8	9	10	12	13	15	16	19	20								
	12	1.25	5 6 8 9 10 12 13 15 16 19 20										12			18	23	26.6				
	14			5 6 8 9 10 12 13 15 16 19 20										13			21	26	30			
	16	1.5	8 9 10 12 13 15 16 19 20										15	5	25	30	34.6					
	18		8 9 10 12 13 15 16 19 20																			
	22		12 15 20															17	6	27	32	36.9



Please order according to the diagram

①~⑤ Select the type and parameters in the order of for ordering.

Model(①Code) — ②M — ③Thread pitch — ④L — ⑤T
DQFBG — M4 — 0.7 — L4 — T10



Discounted Price
Quantity 1~9 10~
Price 100% Separate Quotation
Price Excluding Tax (Yuan)

■ T-Dimension Specified Type

Code	Type		Material		Surface Treatment	Surface hardness
	Internal Thread Type	T-Dimension Specified Type	International	Equivalent		
DQFBG			45	S45C	Hard Chromium Plating	750HV~

⑤ t+L+T≤3M When, the threaded hole becomes a through-hole.

Model			L							T	t	D	S	e
Code	M	Thread pitch								Minimum Unit 1				
DQFBG	4	0.7	3	4	5	6	8	9	10	3~40	3	7	10	11.5
	5	0.8	3	4	5	6	8	9	10		8	12	13.9	
	6	1.0	3	4	5	6	8	12	10		14	16.2		
	8	1.0	4	5	6	8				4	13	17	19.6	
		1.25	4	5	6	8	9	10	12		13			
	10	1.25	4	5	6	8	9	10	12		15	16	21	24.2
		1.5	5	6	8	10								