

Hanging Wall Pin ▶ Screw-fixed Type

Flange type



Please order according to the diagram

①~⑥ Select the type and parameters in the order of for ordering

Model(①Code) - ②Specification - ③Dg6 - ④Y - ⑤F - ⑥M - YC AD

NRBFH - 6 - D6 - Y65 - F160 - M4 - YC



Discounted Price

Quantity	1~9	10~
Price	100%	Separate Quotation

Price Excluding Tax (¥/mm)






CAD 2D

Code	Type	Material		Surface Treatment
		International	Equivalent	
NRBFH	Screw-fixed Type	45	S45C	Black Oxide Finish
NRBFJ		0Cr18Ni9	SUS304	Electroless Nickel Plating
NRBFK		45	S45C	Black Oxide Finish
NRBGH	Opposite Edge Flange Type	0Cr18Ni9	SUS304	Electroless Nickel Plating
NRBGJ		45	S45C	Black Oxide Finish
NRBGK		0Cr18Ni9	SUS304	Electroless Nickel Plating

Round Flange Type

Opposite Edge Flange Type



Model ①Code	②Specification	③Dg6	Minimum Unit 1		⑥M	V	H	T	M1	d1	d2	h	P.C.D
			④Y	⑤F									
Round Flange Type	6	6	-0.004 -0.012		3	8	26		M4	6.5	3.5	3.5	17
	6A	6	-0.004 -0.012				32						23
	8	8	-0.005 -0.014	5~160	4	10	28		M5	8	4.3	4.4	19
	8A	8	-0.005 -0.014				36		M4	6.5	3.5	3.5	26
	10	10	-0.006 -0.017	12~65	4 5 6	13	32	10					23
	10A	10	-0.006 -0.017				40						30
	12	12	-0.007 -0.020	10~160	5 6 8	15	36						26
	13	13	-0.007 -0.020			16	38						27
	15	15	-0.009 -0.025	17~80	6 8 10	18	40		M5	8	4.3	4.4	30
	16	16	-0.009 -0.025			19	42						31
	17	17	-0.009 -0.025	20~80	8 10 12 16	20	44						32
	18	18	-0.009 -0.025			21	46						34
	20	20	-0.009 -0.025		6 8 10 12	24	48		M6	9.5	5.2	5.4	36
	22	22	-0.009 -0.025		8 10 12 16	26	50						39
	25	25	-0.009 -0.025		8 10 12 16 20	29	54		M8	11	6.8	6.5	42
	30	30	-0.009 -0.025		12 16 20	34	62	15					49
	35	35	-0.009 -0.025		16 20	39	70						55
	40	40	-0.009 -0.025			44	80		M10	14	8.6	9	63
	50	50	-0.009 -0.025			54	90						73

Model ①Code	②Specification	③Dg6	Minimum Unit 1		⑥M	V	H	T	M1	d1	d2	h	W	A
			④Y	⑤F										
Opposite Edge Flange Type	6	6	-0.004 -0.012		3	8	26		M4	6.5	3.5	3.5	13	17
	8	8	-0.005 -0.014	5~160	4	10	28						14	19
	10	10	-0.006 -0.017	12~65	4 5 6	13	32	10					15	23
	12	12	-0.007 -0.020		5 6 8	15	36						19	26
	13	13	-0.007 -0.020			16	38						21	27
	15	15	-0.009 -0.025	10~160	6 8 10	18	40		M5	8	4.3	4.4	23	30
	16	16	-0.009 -0.025			19	42						24	31
	17	17	-0.009 -0.025	17~80	8 10 12 16	20	44						27	32
	18	18	-0.009 -0.025			21	46						30	34
	20	20	-0.009 -0.025	20~80	6 8 10 12	24	48		M6	9.5	5.2	5.4	31	36
	22	22	-0.009 -0.025		8 10 12 16	26	50						33	39
	25	25	-0.009 -0.025		8 10 12 16 20	29	54		M8	11	6.8	6.5	37	42
	30	30	-0.009 -0.025		12 16 20	34	62	15					41	49
	35	35	-0.009 -0.025		16 20	39	70						49	55
	40	40	-0.009 -0.025			44	80		M10	14	8.6	9	55	63
	50	50	-0.009 -0.025			54	90						69	73

Optional Processing	Code		Technical Specification	
YC	Change Y Dimension Tolerance		Selection Method YC	
			① Change Y Dimension Tolerance to ± 0.04	
AD	Add a guide section		Selection Method AD	