

Threaded Sleeve ▶ Self-tapping 307 Standard Type / Self-tapping 308 Reinforced Type



Please order according to the diagram

①~③ Select the type and parameters in the order of for ordering

Model(①Code) — ②M
UXOGC — M3



Discounted Price
Quantity 1~9 10~
Price 100% Separate Quotation
Price Excluding Tax (Yen)

Self-tapping 307 Standard Type

Code	Type	Material	Surface Treatment	Usage
UXOGC UXOGU	Self-tapping 307 Standard Type Three Round Hole Type Coarse Thread	Carbon Steel SUS303	Color-zinc Coated —	Enhanced thread strength

Model		P Pitch	L	N External thread	Reference drilling diameter		Minimum drilling depth	Reference Weight (g)
Code	M				Aluminum Alloy	Cast iron		
UXOGC UXOGU	3	0.5	4	M5×0.6	4.6~4.7	4.7~4.8	6	0.3
	4	0.7	6	M6.5×0.8	6.0~6.1	6.1~6.2	8	0.8
	5	0.8	7	M8×1.0	7.4~7.5	7.6~7.7	9	1.3
	6	1	8	M10×1.25	9.3~9.4	9.5~9.6	10	2.4
	8	1.25	9	M12×1.5	11.1~11.3	11.3~11.5	11	3.2
	10	1.5	10	M14×1.5	13.1~13.3	13.3~13.5	13	4.5
	12	1.75	12	M16×1.75	15.0~15.3	15.3~15.5	15	6.4



Please order according to the diagram

①~③ Select the type and parameters in the order of for ordering

Model(①Code) — ②M
UXOHC — M3



Discounted Price
Quantity 1~9 10~
Price 100% Separate Quotation
Price Excluding Tax (Yen)

Self-tapping 308 Reinforced Type

Code	Type	Material	Surface Treatment	Usage
UXOHC UXOHY	Self-tapping 308 Reinforced Type Three Round Hole Type Coarse Thread	Carbon Steel SUS303	Color-zinc Coated —	Enhanced thread strength

Model		P Pitch	L	N External thread	Reference drilling diameter		Minimum drilling depth	Reference Weight (g)
Code	M				Aluminum Alloy	Cast iron		
UXOHC UXOHY	3	0.5	6	M5×0.6	4.6~4.7	4.7~4.8	8	0.45
	4	0.7	8	M6.5×0.8	6.0~6.1	6.1~6.2	10	1
	5	0.8	10	M8×1.0	7.4~7.5	7.6~7.7	13	1.85
	6	1	12	M10×1.25	9.3~9.4	9.5~9.6	15	4
	8	1.25	14	M12×1.5	11.1~11.3	11.3~11.5	17	5.4
	10	1.5	18	M14×1.5	13.1~13.3	13.3~13.5	22	8
	12	1.75	22	M16×1.75	15.0~15.3	15.3~15.5	26	12.5