

Precision shim ▶ Dimension selection type / Specified dimension type

Square shape



Please order according to the diagram

①~④ Select the type and parameters in the order of for ordering

Model(①Code) — ②T — ③A — ④B
FZWGA — **T0.2** — **A250** — **B50**



Price Excluding Tax (¥/unit)

Discounted Price	Quantity	1~9	10~
Price	100%	Separate Quotation	

Dimension selection type



Code	Type	Sales method	Material	Hardness
FZWGA	Dimension selection type	Single	SK Material	55~62HRC
FZWGB			SUS304H	370~430HV

❑ Tolerance chart

Code	Tolerance					
	0.05	0.1	0.2	0.3	0.5	1.0
FZWGA	—	±0.009	±0.010	±0.018	±0.020	±0.030
FZWGB	±0.002	±0.010	±0.012	±0.020	±0.025	±0.030

❑ A/B Tolerance chart

A.B	A/B Tolerance
20~	±0.5
400~	—
800~	±1.2

Model		A	B
Code	T		
FZWGA (SK Material)	0.1	100	50
	0.2	250	
	0.3	500	
	0.5	1000	

Model		A														B		
Code	T	10	20	30	40	50	60	70	80	90	100	120	150			10	20	30
FZWGB (SUS304H)	0.05																	
	0.1																	
	0.2																	
	0.3																	
	0.5																	
	1.0																	



Please order according to the diagram

①~④ Select the type and parameters in the order of for ordering

Model(①Code) — ②A — ③B — ④T
FZXHA — **A250** — **B50** — **T0.2**



Price Excluding Tax (¥/unit)

Discounted Price	Quantity	1~9	10~
Price	100%	Separate Quotation	

Specified dimension type



Code	Type	Sales method	Material	Hardness
FZXHA	Specified dimension type	Single	SK Material	55~62HRC
FZXHB			SUS304H	370~430HV

❑ Tolerance chart

Code	Tolerance					
	0.05	0.1	0.2	0.3	0.5	1.0
FZXHA	—	±0.009	±0.010	±0.018	±0.020	±0.030
FZXHB	±0.002	±0.010	±0.012	±0.020	±0.025	±0.030

❑ A/B Tolerance chart

A.B	A/B Tolerance
20~	±0.5
400~	±0.8
800~	±1.2

Model		Minimum Unit 1		T
Code		A	B	
FZXHA (SK材)				0.1
				0.2
				0.3
				0.5
				1.0

Model		Minimum Unit 1		T
Code		A	B	
FZXHB (SUS304H)		5~100	5~100	0.1
		101~200	20~200	0.2
		201~1000	20~300	0.3
				0.5
		1001~1200	301~400	1.0

① A≥B

① A≥B