

Precision shim ▶ Shim ring



Please order according to the diagram

①~④ Select the type and parameters in the order of for ordering

Model(●Code) — ②d — ③D — ④T
FZZKA — d2 — D4 — T0.2



Quantity	1~9	10~
Price	100%	Separate Quotation


Price Excluding Tax (¥/unit)



CAD 2D 3D

Code	Type	Material		Hardness
		National Standard	Equivalent	
FZZKA	Shim ring	0Cr18Ni9	SUS304H	350~400HV
FZZKB		H62	Brass (C2801P or C2680P)	—

① Due to process and batch issues, a small portion of products may have a 0.1 ~ 1mm gap at the back edge.



■ Tolerance chart

Code	Tolerance								
	0.01	0.02	0.03	0.05	0.1	0.2	0.3	0.5	1.0
FZZKA	±0.003	±0.003	±0.005	±0.005	±0.02	±0.03	±0.035	±0.04	±0.05
FZZKB	—	—	—	—	—	—	±0.04	±0.05	±0.08

Model	Code		d	D	T
FZZKA FZZKB	FZZKA	FZZKB	2	3 4 5 6	(0.01) (0.02) (0.03) Only FZZKA (0.05) Only FZZKA/FZZKB 0.1 0.2 0.3 0.5 1.0
			3	4 5 6 7 8 10	
			4	6 7 8 10 12	
			5	7 8 10 12 14 16	
			6	8 10 12 14 16	
			8	12 14 16 18 20	
			10	12 14 16 18 20	
			12	16 18 20 21 22	
			15	18 20 21 22 24	
			16	20 21 22 24 28	
	FZZKB	FZZKB	17	20 21 22 24 28 30 32	
			20	24 28 30 32 35 40	
			22	28 30 32 35 40	
			25	30 32 35 40 42	
			28	32 35 40 42 45	
			30	35 40 42 45 50	
			35	42 45 50 55	
			40	45 50 55	
			45	50 55	

① Equal d=2, D=3 when, Thickness T0.5, T1.0 Not Applicable FZZKA.

① Equal d=3, D=4 when, Thickness T0.5, T1.0 Not Applicable FZZKA.