

Circular Posts

One End Internal Thread · One End External Thread Type Both Ends Internal Thread Type · L Dimension Specified Type



Please order according to the diagram

①~⑤ Select the type and parameters in the order for ordering. ■ Optional Processing

Model(①Code) — ②D — ③L — ④SC — ⑤M — MC()
KPAAP — D5 — L60 — SC50 — M2.6 — MC4



● Discounted Price
Quantity 1~9 10~
Price 100% Separate Quotation
Price Excluding Tax (¥/mm)

One End Internal Thread / One End External Thread Type

	With Spanner Slot Type		Material		Surface Treatment	L	Tolerance
	One End Internal Thread	One End External Thread Type	International	Equivalent			
	KPAAP	KPBAP			—	15~300	±0.2
	KPAAQ	KPBAQ	Q235	SS400	Black Oxide Finish	301~600	±0.3
	KPAAR	KPBAR			Electroless Nickel Plating	601~1020	±0.4
	KPAAS	KPBAS	0Cr18Ni9	SUS304	—		

One End Internal Thread

One End External Thread Type

① Q235 materials are shipped with rust-preventive oil applied.

Model	Minimum Unit 1			M	W	V1
	Code	D	SC			
One End Internal Thread	5	15~60	0~50	2.6 3	4	10
	6	20~160	0~150	3 4 5	5	7
	8	20~360	0~350	4 5 6	8	10
	12	25~420	0~398	5 6 8	10	12
	15	35~520	0~508	6 8 10	13	16
One End External Thread Type	20	40~520	0~608	6 8 10 12	17	20
	25	55~620	0~705	6 8 10 12 16	22	27
	30	65~720	0~805	8 10 12 16 20	30	36
	35	80~820	0~900	10 12 16 20 24	36	41
	40	80~920	0~1000	12 16 20 24	41	
	50	80~1020	0~1000			
	50	80~1020	0~1000			

Optional Processing

Code	Technical Specification
MC()	Change External Thread Length Selection Method MC4 ① Minimum Unit 0.1 ② Not Applicable for One End Internal Thread Type ③ Applicable for D5 and Larger Sizes



Please order according to the diagram

①~⑤ Select the type and parameters in the order for ordering

Model(①Code) — ②D — ③L — ④SC — ⑤M
KPCAP — D5 — L60 — SC50 — M2.6



● Discounted Price
Quantity 1~9 10~
Price 100% Separate Quotation
Price Excluding Tax (¥/mm)

Both Ends Internal Thread Type

	L Dimension Specified Type		Material		Surface Treatment	L	Tolerance
	Standard Type	With Spanner Slot Type	International	Equivalent			
	KPCAP	KPCBP			—	8~300	±0.2
	KPCAQ	KPCBQ	Q235	SS400	Black Oxide Finish	300.5~600	±0.3
	KPCAR	KPCBR			Electroless Nickel Plating	600.5~1020	±0.4
	KPCAS	KPCBS	0Cr18Ni9	SUS304	—		
	KPCAT	KPCBT	LY11	A2017	Natural Anodizing		

Standard Type

With Spanner Slot Type

① Q235 materials are shipped with rust-preventive oil applied.

Model	Minimum Unit 0.5			M	W	V1
	Code	D	L			
Standard Type	5	8.0~60.0		2.6	4	10
	6	10.0~160.0		3	5	7
	8	15.0~360.0		4	8	10
	10	25.0~420.0		5	10	12
	12	25.0~520.0		6	13	16
	15	30.0~520.0		8	17	20
	20	40.0~620.0		10	22	27
	25	50.0~720.0		12	30	36
	30	50.0~820.0		16	36	41
	35	60.0~920.0		20		
	40	75.0~1020.0		24		

Model	Minimum Unit 0.5			M	W	V1
	Code	D	SC			
With Spanner Slot Type	5	8.0~60.0	0~50	2.6	4	10
	6	10.0~160.0	0~150	3	5	7
	8	15.0~360.0	0~350	4	8	10
	10	25.0~420.0	0~398	5	10	12
	12	25.0~520.0	0~408	6	13	16
	15	30.0~520.0	0~508	8	17	20
	20	40.0~620.0	0~610	10	22	27
	25	50.0~720.0	0~705	12	30	36
	30	50.0~820.0	0~805	16	36	41
	35	60.0~920.0	0~900	20		
	40	75.0~1020.0	0~1000	24		