

Circular Posts ▶ One End Internal Thread · One End External Thread Type

Both Ends Internal Thread Type · L Dimension Specified Type



Please order according to the diagram

①~⑤ Select the type and parameters in the order for ordering. ⑥ Optional Processing

Model(①Code) - ②D - ③L - ④SC - ⑤M - ⑥MC()
KPAAP - D5 - L60 - SC50 - M2.6 - MC4



Quantity	1~9	10~
Price	100%	Separate Quotation

Disco/Unit Price
Price Excluding Tax (¥/unit)

One End Internal Thread / One End External Thread Type

	With Spanner Slot Type		Material		Surface Treatment	L	Tolerance
	One End Internal Thread	One End External Thread Type	International	Equivalent			
	KPAAP	KPBAP			—	15~300	±0.2
	KPAAQ	KPBAQ	Q235	SS400	Black Oxide Finish	301~600	±0.3
	KPAAR	KPBAR			Electroless Nickel Plating	601~1020	±0.4
	KPAAS	KPBAS	0Cr18Ni9	SUS304	—		

One End Internal Thread

One End External Thread Type

① Q235 materials are shipped with rust-preventive oil applied.

Model	Minimum Unit 1			M	W	V1
	Code	D	SC			
One End Internal Thread	5	15~60	0~50	2.6 3	4	
	6	20~160	0~150	3 4	5	10
	8	20~160	0~150	3 4 5	7	
	10	20~360	0~350	4 5 6	8	
	12	25~420	0~398	5 6 8	10	
One End External Thread Type	15	35~520	0~508	6 8 10	13	12
	20	40~520		6 8 10 12	17	
	25	55~620	0~608	6 8 10 12 16	22	
	30	65~720	0~705	6 8 10 12 16 20	27	
	35	80~820	0~805	8 10 12 16 20	30	16
	40	80~920	0~900	10 12 16 20 24	36	
	50	80~1020	0~1000	12 16 20 24	41	20

Optional Processing

Code	Technical Specification	
MC()	Change External Thread Length	Selection Method MC4
		① Minimum Unit 0.1 ② Not Applicable for One End Internal Thread Type ③ Applicable for D5 and Larger Sizes



Please order according to the diagram

①~⑤ Select the type and parameters in the order for ordering

Model(①Code) - ②D - ③L - ④SC - ⑤M
KPCAP - D5 - L60 - SC50 - M2.6



Quantity	1~9	10~
Price	100%	Separate Quotation

Disco/Unit Price
Price Excluding Tax (¥/unit)

Both Ends Internal Thread Type

	L Dimension Specified Type		Material		Surface Treatment	L	Tolerance
	Standard Type	With Spanner Slot Type	International	Equivalent			
	KPCAP	KPCBP			—	8~300	±0.2
	KPCAQ	KPCBQ	Q235	SS400	Black Oxide Finish	300.5~600	±0.3
	KPCAR	KPCBR			Electroless Nickel Plating	600.5~1020	±0.4
	KPCAS	KPCBS	0Cr18Ni9	SUS304	—		
	KPCAT	KPCBT	LY11	A2017	Natural Anodizing		

Standard Type

With Spanner Slot Type

① Q235 materials are shipped with rust-preventive oil applied.

Model	Minimum Unit 0.5			M	W	V1
	Code	D	L			
Standard Type	5		8.0~60.0	2.6	4	
	6		10.0~160.0	3	5	10
	8		10.0~160.0	4	7	
	10		15.0~360.0	5	8	
	12		25.0~420.0	6	10	
	15		25.0~520.0	8	13	12
	20		30.0~520.0	10	17	
	25		40.0~620.0	12	22	
	30		50.0~720.0	16	27	16
	35		50.0~820.0	16	30	
	40		60.0~920.0	20	36	20
	50		75.0~1020.0	24	41	

Model	Minimum Unit 0.5			M	W	V1
	Code	D	SC			
With Spanner Slot Type	5		8.0~60.0	2.6	4	
	6		10.0~160.0	3	5	10
	8		10.0~160.0	4	7	
	10		15.0~360.0	5	8	
	12		25.0~420.0	6	10	
	15		25.0~520.0	8	13	12
	20		30.0~520.0	10	17	
	25		40.0~620.0	12	22	
	30		50.0~720.0	16	27	16
	35		50.0~820.0	16	30	
	40		60.0~920.0	20	36	20
	50		75.0~1020.0	24	41	