

Circular Posts ▶ Standard Type · With Spanner Slot Type

One End External Thread, One End Internal Thread Type · Thread Specified Type



Please order according to the diagram

①~⑥ Select the type and parameters in the order for ordering.

Model(①Code) — ②D — ③L — ④F — ⑤M — ⑥N — AC(LD)
KPDEP — D6 — L60 — F30 — M4 — N4 — LD35

Optional Processing



Disc/Unit Price
 Quantity 1~9 10~
 Price 100% Separate Quotation
 Price Excluding Tax (Yen)

Standard Type

Code

Type

Material

Surface Treatment

Code	Type	Material	Surface Treatment
KPDEP	Thread Length Specified Type	Q235	Black Oxide Finish
KPDEQ		SS400	Electroless Nickel Plating
KPDER		0Cr18Ni9	—
KPDES	Standard Type	SUS304	—

L

Tolerance

15~300 ±0.2

300.5~600 ±0.3

600.5~1020 ±0.4

① Q235 materials are shipped with rust-preventive oil applied.

Model	D	L	F	M	N	E
Code						
5	15.0~60.0	5.0~25.0	2.6 3	2.6 3		1.0
6	5.0~30.0	5.0~30.0	3 4	3 4		
8	20.0~160.0	8.0~40.0	4 5	4 5		1.6
10	20.0~360.0	8.0~45.0	4 5 6	4 5 6		2.0
12	25.0~420.0	10.0~55.0	5 6 8	5 6 8		2.5
15	30.0~520.0	12.0~60.0	6 8 10	6 8 10		3.0
20	40.0~520.0	15.0~75.0	6 8 10 12	6 8 10 12		3.5
25	55.0~620.0	20.0~80.0	6 8 10 12 16	6 8 10 12 16		4.0
30	65.0~720.0	25.0~90.0	6 8 10 12 16 20	6 8 10 12 16 20		5.0
35	80.0~820.0	30.0~100.0	8 10 12 16 20 24	8 10 12 16 20 24		
40	80.0~920.0	35.0~110.0	10 12 16 20 24	10 12 16 20 24		6.0
50	80.0~1020.0	40.0~120.0	12 16 20 24	12 16 20 24		

① Optional Processing Details are provided in the following table.



Please order according to the diagram

①~⑥ Select the type and parameters in the order for ordering

Model(①Code) — ②D — ③L — ④F — ⑤SC — ⑥M — ⑦N — AC(LD)
KPDFP — D6 — L60 — F30 — SC50 — M4 — N4 — LD35

Optional Processing



Disc/Unit Price
 Quantity 1~9 10~
 Price 100% Separate Quotation
 Price Excluding Tax (Yen)

With Spanner Slot Type

Code

Type

Material

Surface Treatment

Code	Type	Material	Surface Treatment
KPDFP	Thread Length Specified Type	Q235	Black Oxide Finish
KPDFQ		SS400	Electroless Nickel Plating
KPDFR		0Cr18Ni9	—
KPDFS	With Spanner Slot Type	SUS304	—

L

Tolerance

15~300 ±0.2

300.5~600 ±0.3

600.5~1020 ±0.4

① Q235 materials are shipped with rust-preventive oil applied.

Model	D	L	F	SC	M	N	W	V1	E
Code									
5	15.0~60.0	5.0~25.0	0~50.0	2.6 3	2.6 3		4		1.0
6	5.0~30.0	5.0~30.0	0~150.0	3 4	3 4		5	10	
8	20.0~160.0	8.0~40.0	0~350.0	4 5	4 5		7		1.6
10	20.0~360.0	8.0~45.0	0~408.0	4 5 6	4 5 6		8		2.0
12	25.0~420.0	10.0~55.0	0~508.0	5 6 8	5 6 8		10		2.5
15	30.0~520.0	12.0~60.0	0~610.0	6 8 10	6 8 10		13		3.0
20	40.0~520.0	15.0~75.0	0~705.0	6 8 10 12	6 8 10 12		17	12	3.5
25	55.0~620.0	20.0~80.0	0~805.0	6 8 10 12 16	6 8 10 12 16		22		4.0
30	65.0~720.0	25.0~90.0	0~900.0	6 8 10 12 16 20	6 8 10 12 16 20		27	16	5.0
35	80.0~820.0	30.0~100.0	0~1000.0	8 10 12 16 20 24	8 10 12 16 20 24		30		
40	80.0~920.0	35.0~110.0		10 12 16 20 24	10 12 16 20 24		36	20	6.0
50	80.0~1020.0	40.0~120.0		12 16 20 24	12 16 20 24		41		

Optional Processing	Code	Technical Specification	
AC	LD()	Addition of Undercut Selection Method AC Processing A Dimension Root Undercut.	Addition of Through Hole for Hexagonal Spanner Selection Method LD35 ① Minimum Unit 1 ② Scope of Application: D8~30 ③ When specifying d dimension, please note the LD dimension to avoid interference or contact with screw holes.