

Circular Posts ▶ Standard Type · With Spanner Slot Type

External Threads at Both Ends



Please order according to the diagram

①~⑥ Select the type and parameters in the order for ordering. ■ Optional Processing

Model(①Code) — ②D — ③L — ④F — ⑤M — ⑥N — AC LD()

KPEAP — D6 — L60 — F30 — M4 — N4 — LD35



● Discounted Price
Quantity 1~9 10~
Price 100% Separate Quotation

Price Excluding Tax (Yen)

■ Standard Type

Code	Type	Material		Surface Treatment
		International	Equivalent	
KPEAP KPEAQ KPEAR KPEAS	Two-end External Thread Type Standard Type	Q235 0Cr18Ni9	SS400 SUS304	Black Oxide Finish Electroless Nickel Plating —

L	Tolerance
15~300	±0.2
300.5~600	±0.3
600.5~1020	±0.4

① Q235 materials are shipped with rust-preventive oil applied.
② Optional Processing Details are provided in the following table.

Model	Minimum Unit 0.5			M		N		E
Code	D	L	F					
KPEAP KPEAQ KPEAR KPEAS	5	15.0~60.0	5.0~25.0	2.6	3	2.6	3	1.0
	6	20.0~160.0	8.0~40.0	3	4	3	4	1.6
	8	20.0~360.0	8.0~45.0	4	5	4	5	2.0
	10	25.0~420.0	10.0~55.0	4	5	4	5	2.5
	12	30.0~520.0	12.0~60.0	5	6	5	6	3.0
	15	40.0~520.0	15.0~75.0	6	8	6	8	3.5
	20	55.0~620.0	20.0~80.0	6	8	6	8	4.0
	25	65.0~720.0	25.0~90.0	8	10	8	10	5.0
	30	80.0~820.0	30.0~100.0	8	10	8	10	6.0
	35	80.0~920.0	35.0~110.0	10	12	10	12	
	40	80.0~1020.0	40.0~120.0	12	16	12	16	



Please order according to the diagram

①~⑦ Select the type and parameters in the order for ordering. ■ Optional Processing

Model(①Code) — ②D — ③L — ④F — ⑤SC — ⑥M — ⑦N — AC LD()

KPEBP — D6 — L60 — F30 — SC50 — M4 — N5 — LD35



● Discounted Price
Quantity 1~9 10~
Price 100% Separate Quotation

Price Excluding Tax (Yen)

■ With Spanner Slot Type

Code	Type	Material		Surface Treatment
		International	Equivalent	
KPEBP KPEBQ KPEBR KPEBS	Two-end External Thread Type With Spanner Slot Type	Q235 0Cr18Ni9	SS400 SUS304	Black Oxide Finish Electroless Nickel Plating —

L	Tolerance
15~300	±0.2
300.5~600	±0.3
600.5~1020	±0.4

① Q235 materials are shipped with rust-preventive oil applied.

Model	Minimum Unit 0.5			M		N		W	V ₁	E
Code	D	L	F							
KPEBP KPEBQ KPEBR KPEBS	5	15.0~60.0	5.0~25.0	0~50.0	2.6	3	2.6	3	4	1.0
	6	20.0~160.0	8.0~40.0	0~150.0	3	4	3	4	5	1.6
	8	20.0~360.0	8.0~45.0	0~350.0	4	5	4	5	7	2.0
	10	25.0~420.0	10.0~55.0	0~408.0	4	5	4	5	8	2.5
	12	30.0~520.0	12.0~60.0	0~508.0	5	6	5	6	10	3.0
	15	40.0~520.0	15.0~75.0	0~610.0	6	8	6	8	13	3.5
	20	55.0~620.0	20.0~80.0	0~705.0	6	8	6	8	17	4.0
	25	65.0~720.0	25.0~90.0	0~805.0	8	10	8	10	22	5.0
	30	80.0~820.0	30.0~100.0	0~900.0	8	10	8	10	27	6.0
	35	80.0~920.0	35.0~110.0	0~1000.0	10	12	10	12	30	
	40	80.0~1020.0	40.0~120.0	0~1000.0	12	16	12	16	36	

Optional Processing

Code	Technical Specification		Code	Technical Specification	
AC	Addition of Undercut		LD()	Addition of Through Hole for Hexagonal Spanner	
	Selection Method AC Processing A Dimension Root Undercut 			Selection Method LD35 ① Minimum Unit 1 ② Scope of Application: D8~30 ③ When specifying d dimension, please note the LD dimension to avoid interference or contact with screw holes. 	